



SEMIPACK® 5

Rectifier Diode Modules

SKKD 701

Features

- Heat transfer through aluminium nitride ceramic insulated metal baseplate
- Precise metal pressure contacts for high reliability
- UL recognized, file no. E63532

Typical Applications

- Uncontrolled rectifiers for AC/AC converters
- Line rectifiers for transistorized AC motor controller
- Field supply for DC motors







1) see assembly instructions
2) screws must be lubricated




V_{RSM} V	V_{RRM} V	$I_{FRMS} = 1100\text{ A}$ (maximum value for continuous operation) $I_{FAV} = 701\text{ A}$ (sin. 180; $T_C = 100\text{ °C}$)		
1300	1200	SKKD 701/12		
1700	1600	SKKD 701/16		
1900	1800	SKKD 701/18		
2300	2200	SKKD 701/22 H4		


Symbol	Conditions	Values	Units
I_{FAV}	sin. 180; $T_C = 100\text{ (85) °C}$	701 (820)	A
I_{FSM}	$T_{vj} = 25\text{ °C}$; 10 ms	25000	A
	$T_{vj} = 160\text{ °C}$; 10 ms	22500	A
i^2t	$T_{vj} = 25\text{ °C}$; 8,3 ... 10 ms	3125000	A²s
	$T_{vj} = 160\text{ °C}$; 8,3 ... 10 ms	2531250	A²s
V_F	$T_{vj} = 25\text{ °C}$; $I_F = 2000\text{ A}$	max. 1,25	V
$V_{(TO)}$	$T_{vj} = 160\text{ °C}$	max. 0,7	V
r_T	$T_{vj} = 160\text{ °C}$	max. 0,28	mΩ
I_{RD}	$T_{vj} = 160\text{ °C}$; $V_{RD} = V_{RRM}$	max. 30	mA
$R_{th(j-c)}$	cont.; per diode / per module	0,069 / 0,034	K/W
	sin. 180; per diode / per module	0,072 / 0,036	K/W
	rec. 120; per diode / per module	0,077 / 0,038	K/W
$R_{th(c-s)}$	per diode / per module	0,02 / 0,01	K/W
T_{vj}		- 40 ... + 160	°C
T_{stg}		- 40 ... + 125	°C
V_{isol}	a.c. 50 Hz, r.m.s.; 1 s / 1 min.	3600 / 3000	V~
V_{isol}	a.c. 50 Hz, r.m.s.; 1 s / 1 min. for SKK... H4	4800 / 4000	V~
M_s	to heatsink	5 ± 15 % ¹⁾	Nm
M_t	to terminals	12 ± 15 % ²⁾	Nm
a		5 * 9,81	m/s²
m	approx.	1400	g
Case		A 75b	



SKKD







This technical information specifies semiconductor devices but promises no characteristics. No warranty or guarantee expressed or implied is made regarding delivery, performance or suitability.