

# SURMOUNT™ 25µM PIN Diodes RoHS Compliant

### Features

- ♦ 0603 Surface Mount 25µm I-Region Length Devices
- No Wirebonds Required
- Rugged Silicon-Glass Construction
- Silicon Nitride Passivation
- Polymer Scratch Protection
- Low Parasitic Capacitance and Inductance
- High Average and Peak Power Handling

### Description

This device is a Silicon-Glass PIN diode chip fabricated with M/A-COM's patented HMIC<sup>™</sup> process. This device features two silicon pedestals embedded in a low loss, low dispersion glass. The diode is formed on the top of one pedestal and connections to the backside of the device are facilitated by making the pedestal sidewalls electrically conductive. Selective backside metallization is applied producing a surface mount device. This vertical topology provides for exceptional heat transfer. The topside is fully encapsulated with silicon nitride and has an additional polymer layer for scratch and impact protection. These protective coatings prevent damage to the junction and the anode air-bridge during handling and assembly.

### **Applications**

These packageless devices are suitable for usage in high incident power, 40dBm C.W., or  $50dBm,10\mu$ S, 1% duty cycle, peak power applications, when used as series, shunt, or series-shunt switches. Smaller parasitic inductance, <0.2nH, and excellent RC time constant, <.3pS make these devices ideally suited for higher frequency switch elements compared to their plastic device counterparts.

Absolute Maximum Rati (unless otherwise specified)	ings <sup>1</sup> @ TA = +25°C
Parameter	Absolute Maximum

Parameter	Absolute Maximum						
Forward Current	500 mA						
Reverse Voltage	- 135 V						
Operating Temperature	-55°C to +125°C						
Storage Temperature	-55 °C to +150°C						
Junction Temperature	+175°C						
	+44dBm MADP-017025						
C.W. Incident Power	+47dBM MADP-030025						
Peak Incident Power (dBm)	+50 dBm, 10µS, 1% duty						
Mounting Temperature	+280°C for 30 seconds						
1) Exceeding these limits may cause permanent damage							

ADVANCED: Data Sheets contain information regarding a product M/A-COM is considering for development. Performance is based on target specifications, simulated results, and/or prototype measurements. Commitment to develop is not guaranteed.

measurements. Commitment to develop is not guaranteed. **PRELIMINARY:** Data Sheets contain information regarding a product M/A-COM has under development. Performance is based on engineering tests. Specifications are typical. Mechanical outline has been fixed. Engineering samples and/or test data may be available. Commitment to produce in volume is not guaranteed.



Case Style ODS 1314

- Backside Contacts are Circuit Side

#### **Chip Dimensions**

DIM	INC	HES	М	Μ	
	Min	Max	Min	Max	
А	0.060	0.062	1.525	1.575	
В	0.031	0.032	0.775	0.825	
С	0.004	0.008	0.102	0.203	
D	0.019	0.021	0.475	0.525	
E	0.019	0.021	0.475	0.525	
F	0.019	0.021	0.475	0.525	
G	0.029	0.031	0.725	0.775	

#### Notes:

- 1) Backside metal: 0.1microns thick.
- Yellow area with hatch lines indicate backside ohmic gold contacts.
- 3) Both devices have same outline dimensions (A to G).

• North America Tel: 800.366.2266 / Fax: 978.366.2266

- Europe Tel: 44.1908.574.200 / Fax: 44.1908.574.300
- Asia/Pacific Tel: 81.44.844.8296 / Fax: 81.44.844.8298
- Visit www.macom.com for additional data sheets and product information.

M/A-COM Inc. and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice.

M/A-COM Products Rev 3

# MADP-017025-1314 MADP-030025-1314



## SURMOUNT<sup>™</sup> 25µM PIN Diodes **RoHS** Compliant

M/A-COM Products Rev 3

Parameter	Symbol	Conditions	Units	Min	Тур	Max	Min	Тур	Max	
				MADP-017025			MADP-030025			
Capacitance <sup>1</sup>	Ст	- 40V, 1MHz <sup>1</sup>	pF		0.23	0.29		0.50	0.56	
Capacitance <sup>1</sup>	Ст	- 40V, 1GHz <sup>1,3</sup>	pF		0.23			0.50		
Capacitance <sup>1</sup> , 85°C	Ст	- 40V, 1GHz <sup>1,3</sup>	pF		0.22			-		
Resistance <sup>2</sup>	Rs	+10mA, 1GHz <sup>2,3</sup>	Ω		1.01			0.65		
Resistance <sup>2</sup>	Rs	+70mA, 1GHz <sup>2,3</sup>	Ω		0.64			0.45		
Resistance <sup>2</sup> , 85°C	Rs	+10mA, 1GHz <sup>2,3</sup>	Ω		1.48			-		
Resistance <sup>2</sup> , 85°C	Rs	+70mA, 1GHz <sup>2,3</sup>	Ω		1.03			-		
Forward Voltage	V <sub>F</sub>	+10mA	V		0.74	0.90		0.73	0.90	
Reverse Leakage Current	I <sub>R</sub>	-135V	μA		-	10		-	10	
Third Order Intercept Point	IP3	F1= 1800MHz F2 = 1810MHz Input Power =+39dBm CW I bias = +70mA	dBm		76			77		
C.W. Thermal Resistance	$R_{qJL}$	I <sub>H</sub> =0.5A, I <sub>L</sub> =10mA	°C/W		30			13		
Lifetime	TL	+10mA / -6mA ( 50 % - 90 % V )	mS		2.3			2.8		

## Electrical Specifications @ $T_A = 25^{\circ}C$ (unless otherwise noted)

#### Notes:

Total capacitance, C<sub>T</sub>, is equivalent to the sum of Junction Capacitance, Cj, and Parasitic Capacitance, Cpar. 1)

Series resistance  $R_s$  is equivalent to the total diode resistance : Rs = Rj (Junction Resistance) + Rc (Ohmic Resistance) 2)

Rs and C<sub>T</sub> are measured on an HP4291A Impedance Analyzer with die mounted in an ODS-186 package with 80/20, 3) Au/Sn solder.

Spice Parameter	N	RS	IS	IK	BV	IBV	Ct	CJO	VJ	М	FC	Cpar_Cj
Units	-	Ω	A	(mA)	(Volts)	(μA)	(pF)	(pF)	(Volts)	-	-	(F)
MADP-017025-1314	1.1	1.4	5.1E-15	12.6	175	10	0.38	0.10	0.17	0.50	0.12	2.7E-13
MADP-030025-1314	1.1	1.3	7.8E-15	12.7	175	10	0.80	0.27	0.12	0.50	0.07	5.3E-13

### MADP-0XX025 Series Typical Spice Parameters @ +25°C

ADVANCED: Data Sheets contain information regarding a product M/A-COM is considering for development. Performance is based on target specifications, simulated results, and/or prototype measurements. Commitment to develop is not guaranteed. PRELIMINARY: Data Sheets contain information regarding a product M/A-COM has under develop-

.

ment. Performance is based on engineering tests. Specifications are typical. Mechanical outline has been fixed. Engineering samples and/or test data may be available. Commitment to produce in volume is not guaranteed.

• North America Tel: 800.366.2266 / Fax: 978.366.2266 Europe Tel: 44.1908.574.200 / Fax: 44.1908.574.300

M/A-COM Inc. and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice.

Asia/Pacific Tel: 81.44.844.8296 / Fax: 81.44.844.8298

Visit www.macom.com for additional data sheets and product information.

# MADP-017025-1314 MADP-030025-1314



## SURMOUNT<sup>™</sup> 25µM PIN Diodes **RoHS** Compliant

M/A-COM Products Rev 3



ment. Performance is based on engineering tests. Specifications are typical. Mechanical outline has been fixed. Engineering samples and/or test data may be available. Commitment to produce in volume is not guaranteed.

Visit www.macom.com for additional data sheets and product information.

M/A-COM Inc. and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice.

MADP-017025-1314 MADP-030025-1314



## SURMOUNT<sup>™</sup> 25µM PIN Diodes RoHS Compliant

M/A-COM Products Rev 3

## Assembly Guidelines

### <u>Handling</u>

All semiconductor chips should be handled with care to avoid damage or contamination from perspiration and skin oils. The use of plastic tipped tweezers or vacuum pickups is strongly recommended for individual components. Bulk handling should insure that abrasion and mechanical shock are minimized.

### **Bonding**

Attachment to a circuit board is made simple through the use of surface mount technology. Mounting pads are conveniently located on the bottom surface of these devices and are removed from the active junction locations. These devices are well suited for solder or conductive epoxy attachment onto hard and soft substrates. The use of 60/40, Pb/Sn, 80/20, Au/Sn or any other lead-free solder is recommended to achieve the lowest series resistance and optimum heat sink.

When soldering these devices to a hard substrate, hot gas die bonding is preferred. We recommend utilizing a vacuum tip and applying a force of 40 - 60 grams to the top surface of the device. When soldering, position the die so that its mounting pads are aligned with the circuit board mounting pads and reflow the solder by heating the circuit trace near the mounting pads while applying 40 to 60 grams of force perpendicular to the top surface of the die. Both mounting pads should be heated simultaneously so that the solder under both pads flows at the same time. The solder joint should not be made one at a time. By doing so, would create an un-equal heat flow and potentially create thermal stress to the chip.

Solder reflow should not be performed by causing heat to flow through the top surface of the die. Die should be uniformly heated in a re-flow oven. Proper flow is easily determined looking down from the top since the HMIC glass is transparent and the edges of the mounting pads can be visually inspected through the die after tachment is complete. A typical soldering process profile and handling instructions are provided in Application Notes, <u>M538 Surface Mounting Instructions</u> and <u>M541 Bonding and Handling Procedures</u> on the MA-COM website at www.macom.com/Application%20Notes/default.asp.

Conductive silver epoxy may also be used for die attachment, in lower Incident power applications where the average power is < 1 W. Apply a thin controlled amount approximately 1- 2 mils thick to minimize ohmic and thermal stresses. Take care not to bridge the gap between the chip pads with epoxy. A thin epoxy fillet should be visible around the perimeter of the pads after placement to ensure full coverage. Cure per epoxy per manufacturer's recommended schedule.

## **Ordering Information**

Gel Pack

MADP-017025-13140G MADP-030025-13140G

ADVANCED: Data Sheets contain information regarding a product M/A-COM is considering for development. Performance is based on target specifications, simulated results, and/or prototype measurements. Commitment to develop is not guaranteed. PRELIMINARY: Data Sheets contain information regarding a product M/A-COM has under develop-

PRELIMINARY: Data Sheets contain information regarding a product M/A-COM has under development. Performance is based on engineering tests. Specifications are typical. Mechanical outline has been fixed. Engineering samples and/or test data may be available. Commitment to produce in volume is not guaranteed. • North America Tel: 800.366.2266 / Fax: 978.366.2266

• Europe Tel: 44.1908.574.200 / Fax: 44.1908.574.300

Asia/Pacific Tel: 81.44.844.8296 / Fax: 81.44.844.8298
Visit www.macom.com for additional data sheets and product information.

M/A-COM Inc. and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice.