

Oscillator Specification

Part No. + Packaging: LFSPX0056228REEL

A.

Description

 Standard 2 x 1.6 crystal oscillator in a ceramic package with a seam sealed metal lid, hermetically sealed

Model IQXO-541Model Issue number 2

Frequency Parameters

Frequency
 Frequency Tolerance @ 25°C
 Frequency Stability
 Operating Temperature Range
 20.0MHz
 INCLUSIVE
 ±50.00ppm
 -40.00 to 85.00°C

■ Ageing ±5ppm

- Ageing ±5ppi

Frequency Stability

 Inclusive of tolerance, supply voltage and load variations over the operating temperature range

Electrical Parameters

Supply Voltage
 Supply Voltage Tolerance
 ±10%
 Current Draw
 Standby Current: 10µA max (pad 1 at logic '0')

Output Details

Output Compatability
 Output Load
 Rise and Fall time (10% - 90%)
 Duty Cycle
 CMOS
 15pF max
 5.0ns max
 45/55%

Output Control

 Standby Operation: Logic '1' (≥70%VS) to pad 1 enables oscillator output

Logic '0' (≤30%VS) to pad 1 disables oscillator output; when disabled the oscillator output goes to the high impedance state No connection to pad 1 enables oscillator output

Environmental Parameters

- Vibration: IEC 60068-2-6: 1.5mm amplitude, 10Hz-55Hz, 1min in 3 mutually perpendicular planes, duration 2hrs each plane (total 6hrs)
- Storage Temperature Range: -40 to 85°C
- Impact: Weight of 10g dropped to centre of part from a height of 6mm

Compliance

■ RoHS Status Compliant REACh Status Compliant

Packaging

■ Pack Type: Reel Tape and reel in accordance with


EIA-481-D

Pack Size 3,000

■ Alternative packing option available

This document is correct at the time of printing; please contact your local office for the latest version.

Outline (mm)




Pad Connections

1. Standby Operation


2. GND

3. Output 4. +Vs






Solder Pad Layout




Underside View

Test Circuit



^{*} Inclusive of jigging and equipment capacitance

Wave Form



Sales Office Contact Details:

UK: +44 (0)1460 270200 France: +33 (0)5 34 50 91 18 Germany: +49 (0)7264 9145-0 USA: +1 (0)408.273.4530 Email: info@iqdfrequencyproducts.com Web: www.iqdfrequencyproducts.com

Printed on 19 Feb 13 12:31