

**Description**

- Standard 2.5 x 2.0 oscillator in a ceramic package with a hermetically sealed metal lid.
- Model IQXO-793
- Model Issue number 1

Frequency Parameters

- Frequency 27.0MHz
- Frequency Tolerance @ 25°C INCLUSIVE
- Frequency Stability $\pm 50.00\text{ppm}$
- Operating Temperature Range -40.00 to 85.00°C
- Ageing $\pm 3\text{ppm}$ max per year

Electrical Parameters

- Supply Voltage 2.5V
- Supply Voltage Tolerance $\pm 10\%$
- Current Draw 10mA max

Output Details

- Output Compatibility HCMOS
- Output Load 15pF
- Rise and Fall time (10% - 90%) 10.0ns max
- Duty Cycle 40/60%
- Output Voltage High: 90% of VS min
Output Voltage Low: 10% of VS max

Output Control

- Standby Function (pin1):
No Connection = Output Enabled
>70% VS = Output Enabled
<30% VS = Output Disabled
When disabled output goes to high impedance state)
- Start Up Time: 10ms max

Noise Parameters

- Jitter (Period pk-pk): $\pm 100\text{ps}$ max
- Jitter (Period One Sigma): $\pm 25\text{ps}$ max
- Jitter (Phase 12kHz to 20MHz): 1ps max

Environmental Parameters

- Shock: MIL-STD-202, Method 213
- Vibration: MIL-STD-883, Method 2007
- Storage Temperature Range: -55 to 125°C



Compliance

- RoHS Status Compliant
- REACH Status Compliant

Packaging

- Pack Type: Bulk Loose in bulk pack
- Pack Size 1
- Alternative packing option available

This document is correct at the time of printing; please contact your local office for the latest version.

**Outline (mm)****Sales Office Contact Details:**

UK: +44 (0)1460 270200

Germany: +49 (0)7264 9145-0

France: +33 (0)5 34 50 91 18

USA: +1 (0)408.273.4530

Email: info@iqdfrequencyproducts.comWeb: www.iqdfrequencyproducts.com