



Description

- LVPECL output using a high frequency fundamental crystal to give very low jitter
- Ceramic package with a seam sealed metal lid, hermetically sealed
- Model IQXO-621
- Model Issue number 2

Frequency Parameters

- Frequency 106.250MHz
- Frequency Tolerance @ 25°C INCLUSIVE
- Frequency Stability ± 50.00 ppm
- Operating Temperature Range -40.00 to 85.00°C
- Ageing ± 3 ppm max per year @ 25°C

Electrical Parameters

- Supply Voltage 2.5V
- Supply Voltage Tolerance $\pm 5\%$
- Current Draw 65mA max

Output Details

- Output Compatibility LVPECL
- Output Load 50 Ω terminated to Vs-2.0V
- Rise and Fall time (10% - 90%) 0.5ns max
- Duty Cycle 45/55%
- Standby Operation:
Logic '1' (70% VS min) to pad 1 enables oscillator output
Logic '0' (30% VS max) to pad 1 disables oscillator output; the oscillator output goes to the high impedance state
No connection to pad 1 enables oscillator output
Standby Current 10 μ A max

Output Levels

- Output Voltage:
'0' Level (VoL), +1.095V max
'1' Level (VoH), +1.475V min

Noise Parameters

- Phase Jitter (12kHz to 20MHz): 1ps rms max

Environmental Parameters

- Shock: MIL-STD-202, Method 213, Condition E: 1000G, 0.5ms, 1/2 sine wave
- Vibration: MIL-STD-883, Method 2007, Condition A: 20G
- Storage Temperature Range: -55 to 125°C

Compliance

- RoHS Status Compliant
- REACH Status Compliant


Packaging

- Pack Type: Bulk Loose in bulk pack
- Pack Size 100
- Alternative packing option available


This document is correct at the time of printing; please contact your local office for the latest version.




Outline (mm)



Test Circuit



Wave Form



Sales Office Contact Details:

UK: +44 (0)1460 270200
Germany: +49 (0)7264 9145-0

France: +33 (0)5 34 50 91 18
USA: +1 (0)408.273.4530

Email: info@iqdfrequencyproducts.com
Web: www.iqdfrequencyproducts.com