



Description

- Oven controlled crystal oscillator (OCXO) with voltage control on a FR4 base with a metal lid.

■ Model IQOV-162-4

■ Model Issue number 2

Frequency Parameters

- Frequency 12.80MHz
- Frequency Tolerance @ 25°C $\pm 500.00\text{ppb}$
- Frequency Stability $\pm 20.00\text{ppb}$
- Operating Temperature Range -40.00 to 85.00°C
- Ageing $\pm 5\text{ppb}$ max per day, $\pm 500\text{ppb}$ max per year
- Supply Voltage Variation (measurement referenced to frequency observed with $T_A=25^\circ\text{C}$, V_s varied from 3.13V to 3.47V, $V_C=1.65\text{V}$ and load= 50Ω): $\pm 10\text{ppb}$ max
- Ageing: V_s , V_C , T_A constant measurement referenced to frequency observed with $T_A=25^\circ\text{C}$, $V_s=3.3\text{V}$, $V_C=1.65\text{V}$, load= 50Ω and after 30 days of operation.
- Load Variation (5% load change measurement referenced to frequency observed with $T_A=25^\circ\text{C}$, $V_s=3.3\text{V}$, $V_C=1.65\text{V}$ and load= 50Ω): $\pm 10\text{ppb}$ max
- Short Term Stability - Allan Variance (temperature stability, no EMI/EMC or other interference test after power for 1hr ref. to 25°C ; 1s, using PN9000 equipment): 0.1ppb max / 1sec
- Frequency Tolerance (measurement referenced to frequency observed with $T_A=25^\circ\text{C}$, $V_s=3.3\text{V}$, $V_C=1.65\text{V}$ and after 15 minutes of operation, within 30 days after ex-works): $\pm 500\text{ppb}$
- Frequency Stability: T_A varied from -40°C to 85°C , measurement referenced to frequency observed with $f_{\text{ref}}=(f_{\text{max}}+f_{\text{min}})/2$, $V_s=3.3\text{V}$, $V_C=1.65\text{V}$, load= 50Ω , temperature variable speed less than 2°C per minute.

Electrical Parameters

- Supply Voltage 3.3V
- Supply Voltage Tolerance $\pm 5\%$
- Current Draw:
Warm up: 560mA max
Steady state (@ 25°C): 250mA max
- Warm-Up Time (@ 25°C , $F < \pm 100\text{ppb}$ of final frequency): 5mins max

Frequency Adjustment




- Pulling $\pm 3\text{ppm}$ to $\pm 8\text{ppm}$
- Control Voltage Details $1.65\text{V} \pm 1.65\text{V}$
- Linearity: $\pm 10\%$ max
- Slope: Positive
- Input Impedance: 100k Ω min

Output Details


- Output Compatibility Sine
- Output Load 50Ω
- Output Level: 6dBm min, 10dBm max



Outline (mm)



Pad Connections
 1. Voltage Control
 2. N/C
 3. GND
 4. Output
 5. N/C
 6. +Vs



Sales Office Contact Details:

UK: +44 (0)1460 270200

Germany: +49 (0) 30 408 192 300

France: +33 (0)5 34 50 91 18

USA: +1 408.273.4530

Email: info@iqdfrequencyproducts.com

Web: www.iqdfrequencyproducts.com



Noise Parameters

- Phase Noise (@ 100MHz typ):
 - 90dBc/Hz @ 10Hz
 - 120dBc/Hz @ 100Hz
 - 145dBc/Hz @ 1kHz
 - 150dBc/Hz @ 10kHz
 - 150dBc/Hz @ 100kHz
 - 155dBc/Hz @ 1MHz
- Phase Noise (@ 10MHz typ):
 - 100dBc/Hz @ 10Hz
 - 130dBc/Hz @ 100Hz
 - 145dBc/Hz @ 1kHz
 - 150dBc/Hz @ 10kHz
 - 150dBc/Hz @ 100kHz
 - 155dBc/Hz @ 1MHz
- Harmonic Suppression: -30dBc max
- Spurious Suppression: -60dBc max

Environmental Parameters

- Shock: IEC 60068-2-27, Test Ea, Severity 50A: 50G, 11ms duration, 1/2 sine wave, 3 times in each of 3 mutually perpendicular planes
- Vibration: IEC 60068-2-06, Test Fc: 10Hz-500Hz, 0.75mm displacement, 10G acceleration, one cycle per 30mins, 3 times in each of 3 mutually perpendicular planes, test 2hrs
- Storage Temperature Range: -55 to 105°C
- Operable Temperature Range: -40 to 85°C
- ESD Level:
 - HBM, Class 2: 2000V to 4000V, JEDEC JS-001-2010
 - Machine Model, Class B: 200V to 400V, JEDEC JS-001-2010

Manufacturing Details

- Maximum Reflow Temperature: 260°C (30secs max)
- Moisture Sensitivity Level: 2

Compliance

- | | |
|----------------|-----------|
| ■ RoHS Status | Compliant |
| ■ REACH Status | Compliant |

Packaging

- | | |
|-------------------|--|
| ■ Pack Type: Reel | Tape & reel in accordance with EIA-481-D |
| Pack Size | 500 |

- Alternative packing option available

This document is correct at the time of printing; please contact your local office for the latest version.

Sales Office Contact Details:

UK: +44 (0)1460 270200

Germany: +49 (0) 30 408 192 300

France: +33 (0)5 34 50 91 18

USA: +1 408.273.4530

Email: info@iqdfrequencyproducts.com

Web: www.iqdfrequencyproducts.com