HUBER+SUHNER® DATA SHEET RF ATTENUATOR: Type 6803.19.A



Description

Standard Attenuator, Low Power

Product Configuration

Connectors (side 1 / side 2)

Interface standard

SMA plug (male) / SMA jack (female)

IEC 60169-15 MIL-STD-348A/310 CECC 22110

Technical Data

Electrical Data

 $\begin{array}{ll} \mbox{Nominal impedance} & \mbox{50 } \Omega \\ \mbox{Nominal attenuation} & \mbox{3 dB} \end{array}$

Frequency range DC to 18 GHz

Frequency sub range (GHz) DC to 4 4 to 8 8 to 12.4 12.4 to 18
Attenuation deviation (±dB) 0.3 0.5 0.8
VSWR max. 1.1 1.2 1.2 1.35

Power rating 2 Watt average power up to 30 °C ambient temperature, linearly derated to 0 Watt at 130 °C

ambient temperature.

500 Watt peak power

Mechanical Data

Weight 0.008 kg

Environmental Data

2002/95/EC (RoHS) compliant

Material Data

Piece Part (side 1) Material

Centre contact Copper Beryllium Alloy
Outer contact Copper Beryllium Alloy
Body Copper Beryllium Alloy

Insulator PFA / PTFE Coupling nut Bronze

Piece Part (side 2)MaterialCentre contactCopper Beryllium AlloyOuter contactCopper Beryllium AlloyBodyCopper Beryllium Alloy

Insulator PFA / PTFE

Related Documents

Outline drawing DCA-00005292

Ordering Information

Single packaging 6803.19.A

Surface Plating

Gold Plating (without Nickel underplating) Gold Plating (without Nickel underplating) Gold Plating (without Nickel underplating)

Gold Plating (without Nickel underplating)

Surface Plating

Gold Plating (without Nickel underplating) Gold Plating (without Nickel underplating) Gold Plating (without Nickel underplating)

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

HUBER+SUHNER – Excellence in Connectivity Solutions

Document: DOC-0000227097 J Issued: 16.03.2010 12:23:46 Uncontrolled Copy Page 1/1



HUBER+SUHNER AG RF Industrial 9100 Herisau, Switzerland Phone +41 (0)71 353 41 11 Fax +41 (0)71 353 45 90 www.hubersuhner.com