

HUBER+SUHNER® DATA SHEET

RF ATTENUATOR: Type 6806.01.A

Rev.: H



Description

Standard Attenuator, Low Power

Product Configuration

Connectors (side 1 / side 2) BNC plug (male) / BNC jack (female)
Interface standard IEC 60169-8_MIL-STD-348A/301_CECC 22120

Technical Data

Electrical Data

Nominal impedance 50 Ω
Nominal attenuation 6 dB
Frequency range DC to 4 GHz
Frequency sub range (GHz) DC to 2 2 to 4
Attenuation deviation (\pm dB) 0.3 0.5
VSWR max. 1.1 1.2
Power rating 2 Watt average power up to 30 °C ambient temperature, linearly derated to 0 Watt at 130 °C ambient temperature.

500 Watt peak power

Mechanical Data

Weight 0.025 kg

Environmental Data

2002/95/EC (RoHS) compliant

Material Data

Piece Part (side 1)

Centre contact Copper Beryllium Alloy
Outer contact Brass
Body Brass
Insulator PFA / PTFE
Coupling nut Brass

Piece Part (side 2)

Centre contact Copper Beryllium Alloy
Outer contact Brass
Body Brass
Insulator PFA / PTFE

Surface Plating

Gold Plating (without Nickel underplating)
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating

SUCOPLATE (R) Plating

Surface Plating

Gold Plating (without Nickel underplating)
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating

Related Documents

Outline drawing DOU-00005238

Ordering Information

Single packaging 6806.01.A



HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Industrial
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions