HUBER+SUHNER® DATA SHEET RF ATTENUATOR: Type 6830.17.A



Description

Standard Attenuator, Low Power

Product Configuration

Connectors (side 1 / side 2)

Interface standard

N plug (male) / N jack (female)

IEC 60169-16 MIL-STD-348A/304 CECC 22210



Electrical Data

Nominal impedance 50Ω Nominal attenuation 30 dB

DC to 12.4 GHz Frequency range

Frequency sub range (GHz) DC to 4 4 to 8 8 to 10 10 to 12.4 Attenuation deviation (±dB) 1 1 1 VSWR max. 1.1 1.2 1.2 1.25

1 Watt average power up to 30 °C ambient temperature, linearly derated to 0 Watt at 130 °C Power rating

ambient temperature.

500 Watt peak power

Mechanical Data

Weight 0.069 kg

Environmental Data

2002/95/EC (RoHS) compliant

Material Data

Piece Part (side 1) Material

Centre contact Copper Beryllium Alloy

Outer contact **Brass** Body **Brass** PFA / PTFE Insulator Coupling nut Brass

Piece Part (side 2) Material

Centre contact Copper Beryllium Alloy

Outer contact **Brass** Body Brass Insulator PFA / PTFE

Related Documents

Outline drawing DOU-00005259

Ordering Information

Single packaging 6830.17.A **Surface Plating**

Gold Plating (without Nickel underplating) Gold Plating (without Nickel underplating)

SUCOPLATE (R) Plating

SUCOPLATE (R) Plating

Surface Plating

Gold Plating (without Nickel underplating) Gold Plating (without Nickel underplating)

SUCOPLATE (R) Plating

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVERI

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only

HUBER+SUHNER – Excellence in Connectivity Solutions

Document: DOC-0000227080 H Issued: 16.03.2010 13:31:56 **Uncontrolled Copy** Page 1/1

HUBER+SUHNER

HUBER+SUHNER AG RF Industrial 9100 Herisau, Switzerland Phone +41 (0)71 353 41 11

+41 (0)71 353 45 90 www.hubersuhner.com