


REVISIONS

REV.	DESCRIPTION	DATE	APPROVED
1	Modified per ECN NO. 0627.	11/11/05	HV



Main Capacitance	: 22.50μF ±3%
Secondary Capacitance	: NIL
Volts	:280AC
Leakage Current	:30μA Max.
Frequency	:50/60 HZ
Operating Temperature	: -40 DEG C TO 90 DEG C
Storage Temperature	: -40 DEG C TO 90 DEG C
Operative Life	:60,000 HRS WITH 94% SURVIVAL
Dissipation Factor	:0.1% MAX.
Case Material	:ALUMINIUM
Cover Material	:TERNPLATE
Terminals	: 0.250"x0.031" Quick Connect Blades
Dielectric Fluid	:DIELEKTROL VI
Internal Protection	: UL RECOGNIZED PRESSURE SENSITIVE INTERRUPTER

FOR ADDITIONAL INFO REFER TO:		SIGNATURES	DATE
APPLIED PRACTICES	MODEL	RAGHU. P. H	09/13/2008
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	DETAIL	RAGHU. P. H	09/13/2008
TOLERANCE ON:	CHECKED	RAGHU. P. H	09/13/2008
1 PL DECIMALS $\pm$ 0.1	ENGRS	-	-
2 PL DECIMALS $\pm$ 0.01	MFG	-	-
3 PL DECIMALS $\pm$ 0.001	QUALITY	-	-
ANGLES $\pm$ 0.5	ISSUED	-	-
FRACTIONS $\pm$			
FINISH			
MATERIAL	SOLID MODEL: 2T/CAPACITOR.ASM		



GEM III CAPACITOR OUTLINE DRAWING

14	TITLE
----	-------

SIZE	DRAWING
------	---------

	(
--	---

SCALE: 1:250

REF. No:

97F6863

REV

SHEET 1 OF 1