






REV.	DESCRIPTION	DATE	APPROVAL
1	Modified as per ECN No. 0627	11/11/05	HV
2	Modified as per ECN No. 0668 & 0673	7/18/08	HV

This document is the property of REGAL BELOIT CORPORATION ("RBC") including its subsidiaries and divisions and contains proprietary information of RBC. This document is loaned on the express condition that neither it nor the information contained herein shall be disclosed to others without the express written consent of RBC. If the terms of this loan are violated, the RBC property is so approved expressly by RBC. This document shall be returned to RBC upon request. This document may be subject to certain restrictions under U.S. export control laws and regulations.



SCALE 1.500

SPECIFICATIONS:

"GEM-III Capacitors are manufactured with High Grade Metallized Polypropylene Film"


Main Capacitance	: 1.50 μ F $\pm$ 6%
Secondary Capacitance	: NIL
Volts	:600AC
Leakage Current	:30 μ A Max.
Frequency	:50/60 HZ
Operating Temperature	: -40 DEG C TO 70 DEG C
Storage Temperature	: -40 DEG C TO 90 DEG C
Operative Life	:60,000 HRS WITH 94% SURVIVAL
Dissipation Factor	:0.1% MAX.
Case Material	:ALUMINIUM
Cover Material	:STEEL TIN PLATED
Terminals	: 0.250"x0.031" Quick Connect Blades
Dielectric Fluid	:DIELEKTROL VI
Internal Protection	: UL RECOGNIZED PSI A10000AFC

FOR ADDITIONAL INFO REFER TO:	SIGNATURES	DATE
APPLIED PRACTICES	MODEL	NPS 07/25/01
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	DETAIL	NPS 07/25/01
TOLERANCE ON:	CHECKED	HV 07/25/01
1 PL DECIMALS $\pm$ 0.1	ENGRG	-
2 PL DECIMALS $\pm$ 0.01	MFG	-
3 PL DECIMALS $\pm$ 0.001	QUALITY	-
ANGLES $\pm$ 0.5	ISSUED	-
FRACTIONS $\pm$		
FINISH		
MATERIAL	SOLID MODEL: 2TCAPACITOR.ASM	

**REGAL-BELOIT CORPORATION**

GEM III CAPACITOR OUTLINE DRAWING

SHEET 1 OF 1



THIRD ANGLE PROJECTION