

SPECIFICATION SHEET

# MAFRIN0541: 1930-1990 MHz Single Junction Drop In Isolator

## **Applications**

- Wireless Infrastructure
- Power amplifiers



- Operating frequency range: 1930 to 1990 MHz
- BeO free
- RoHS compliant




Figure 1. Block Diagram

### Table 1. Absolute Maximum Ratings

Parameter	Symbol	Test Condition	Min	Max	Units
Average power	Pavg			200	W
Peak power	Р <sub>РК</sub>			1000	W
Reverse power	P <sub>REV</sub>			100	W
Operating temperature range	T <sub>OP</sub>		-30	+85	°C
Storage temperature range	T <sub>STOR</sub>		-55	+125	°C

Note: Exceeding any of the limits listed here may result in permanent damage to the device or may reduce device reliability.

Skyworks Solutions, Inc. • Phone [781] 376-3000 • Fax [781] 376-3100 • sales@skyworksinc.com • www.skyworksinc.com Revision B • Skyworks Proprietary Information • Products and Product Information are Subject to Change Without Notice • April 2011

## **SPECIFICATION SHEET • MAFRIN0541**

Parameter	Symbol	Test Condition	Min	Typical	Мах	Units
Frequency range	f		1930		1990	MHz
Impedance				50		Ω
Insertion loss	IL				0.25	dB
Isolation	ISO	-10°C to +85°C	20			dB
Isolation	ISO	-30°C to –10°C	18			dB
Return loss	RL	-10°C to +85°C	21			dB
Isolation	ISO	-30°C to –10°C	19			dB
Third order IMD	IMD	2 x 30W CW tones, 5MHz spacing		75		dBc

## Table 2. Electrical Specifications (Note 1)

Note 1: Performance is guaranteed under the conditions listed in this table and over the operating temperature range.

## **Table 3. Plating Specification**


Section	Base Material	Plating
Leads	Copper	Silver
Housing	Steel	Silver


#### Table 4. Ordering Information

Manufacturing Part Number	Evaluation Board Part Number	
MAFRIN-0541	TFX-00037-31	

Skyworks Solutions, Inc. • Phone [781] 376-3000 • Fax [781] 376-3100 • sales@skyworksinc.com • www.skyworksinc.com Skyworks Proprietary Information • Products and Product Information are Subject to Change Without Notice • April 2011

#### **SPECIFICATION SHEET • MAFRIN0541**





All dimensions in millimeters. Tolerance: ±0.2mm unless otherwise specified. Lead thickness is 0.12mm. Model number, lot code and port designation printed on top side of device.

#### Figure 2. Package Dimensions

Copyright © 2011 Skyworks Solutions, Inc. All Rights Reserved.

Information in the document is provided in connection with Skyworks Solutions, Inc. ("Skyworks") products or services. These materials, including the information contained herein, are provided by Skyworks as a service to its customers and may be used for informational purposes only by the customer. Skyworks assumes no responsibility for errors or omissions in these materials or the information contained herein. Skyworks may change its documentation, products, services, specifications or product descriptions at any time, without notice. Skyworks makes no commitment to update the materials or information and shall have no responsibility whatsoever for conflicts, incompatibilities, or other difficulties arising from any future changes.

No license, whether express, implied, by estoppel or otherwise, is granted to any intellectual property rights by this document. Skyworks assumes no liability for any materials, products or information provided hereunder, including the sale, distribution, reproduction or use of any Skyworks products, information or materials, except as may be provided in Skyworks Terms and Conditions of Sale.

THE MATERIALS, PRODUCTS AND INFORMATION ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, WHETHER EXPRESS, IMPLIED, STATUTORY, OR OTHERWISE, INCLUDING FITNESS FOR A PARTICULAR PURPOSE OR USE, MERCHANTABILITY, PERFORMANCE, QUALITY OR NON-INFRIDEEMENT OF ANY INTELLECTUAL PROPERTY RIGHT, ALL SUCH WARRANTIES ARE HEREBY EX-PRESSLY DISCLAIMED. SKYWORKS DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. SKYWORKS SHALL NOT BE LIABLE FOR ANY DAMAGES, INCLUDING BUT NOT LIMITED TO ANY SPECIAL, INDIRECT, INCIDENTAL, STATUTORY, OR CONSEQUENCIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS THAT MAY RESULT FROM THE USE OF THE INFORMATION, WHETHER OR NOT THE RECIPIENT OF MATERIALS HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Skyworks products are not intended for use in medical, lifesaving or life-sustaining applications, or other equipment in which the failure of the Skyworks products could lead to personal injury, death, physical or environmental damage. Skyworks customers using or selling Skyworks products for use in such applications do so at their own risk and agree to fully indemnify Skyworks for any damages resulting from such improper use or sale.

Customers are responsible for their products and applications using Skyworks products, which may deviate from published specifications as a result of design defects, errors, or operation of products outside of published parameters or design specifications. Customers should include design and operating safeguards to minimize these and other risks. Skyworks assumes no liability for applications assistance, customer product design, or damage to any equipment resulting from the use of Skyworks products outside of stated published specifications or parameters.

Skyworks, the Skyworks symbol, and "Breakthrough Simplicity" are trademarks or registered trademarks of Skyworks Solutions, Inc. in the United States and other countries. Third-party brands and names are for identification purposes only, and are the property of their respective owners. Additional information, including relevant terms and conditions, posted at www.skyworksinc.com and incorporated by reference.

Skyworks Solutions, Inc. • Phone [781] 376-3000 • Fax [781] 376-3100 • sales@skyworksinc.com • www.skyworksinc.com Skyworks Proprietary Information • Products and Product Information are Subject to Change Without Notice • April 2011