


UNAUTHORIZED USE OF THIS
DRAWING IS STRICTLY PROHIBITED

DAR	REV	DESCRIPTION	APPVD	DATE
1695	A	INITIAL RELEASE	DG	1-09
4491	B	SEE DAR	DG	8-13



NOTES
1. CONNECTOR TYPE J1 - J4: TYPE SMA

ELECTRICAL SPECIFICATIONS

FREQUENCY:	500 - 2500 MHz.
INSERTION LOSS:	0.30dB MAX.
MAIN LINE VSWR:	1.25:1 MAX.
COUPLING:	40.0 ±1.0dB
DIRECTIVITY:	>18dB
COUPLED FLATNESS:	±0.50dB
POWER:	200 WATT

J1: INPUT
J2: OUTPUT
J3: -40dB (FWD COUPLED)
J4: -40dB (REFL. COUPLED)

MATERIAL AL. ALLOY 6061-T651	DWN	DG	DATE	9-08	<i>Innovative</i> <i>Power Products</i>		
	ENG	TJD	DATE	9-08			
FINISH CHEM FILM, CLEAR, PER MIL-DTL-5541, TYPE 2, REV. F, CLASS 3 (ROHS COMPLIANT)	MANUF	TP	DATE	9-08	TITLE DUAL DIRECTIONAL COUPLER 500 - 2500 MHZ. 200 WATT, 40 DB		
	CAGE CODE: 437R2						
TOLERANCE .XX ±.02 .XXX ±.010 ANG. ±1/2°	SHEET	OF	SCALE	1:1	SIZE B	P/N IPP-3071	REV. B
	1	1					