

ALL DESIGN, OPERATIVE AND PROCESS DATA PERTAINING TO THE ARTICLE SHOWN ON THIS SHEET IS THE PROPERTY OF POLYPHASER CORPORATION. THE INFORMATION IS NOT TO BE COPIED, REPRODUCED, REVEALED TO OR APPROPRIATED BY OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF POLYPHASER CORPORATION.

# REVISIONS





| REV | LTR | DATE                   | ENG | MKTG | Q.A. |
|-----|-----|------------------------|-----|------|------|
| A   |     | 08/28/06 <sup>SH</sup> | LC  | SD   | LJ   |

## MAXIMUM CHARACTERISTICS DATA (IX-H)

TURN-ON(@10mA):  
+9Vdc ±10%  
UL 497B STRIKE VOLTAGE BREAKDOWN  
(100 Vdc /SEC RISE):  
+8.4 TO +9.6 Vdc  
RESISTANCE:  
1Ω ±20%  
DATA RATE:  
UP TO 100Mbps  
MAX HOLDING CURRENT:  
400mA @ +20°C  
620mA @ -40°C  
290mA @ +50°C  
235mA @ +65°C

## GENERAL CHARACTERISTICS

SURGE:  
BELLCORE 1089 10/1000μs 100A  
TEMPERATURE:  
-40°C TO +65°C STORAGE/OPERATING  
WIRE RANGE:  
16 TO 28 AWG.  
CORD DIAMETER:  
0.114 TO 0.225 INCH W/ SMALL GROMMET  
0.250 TO 0.350 INCH W/ LARGE GROMMET  
APPLICATION:  
PANEL MOUNT.  
WEATHERIZED AFTER PROPER INSTALLATION OF  
GROMMETS AND TORQUING OF LID.  
ENVIRONMENTAL:  
MEETS BELLCORE #TA-NWT-000487 PROCEDURE 4.11,  
WIND DRIVEN RAIN (70MPH) RAIN INTRUSION TEST.



CUSTOMER APPROVAL: \_\_\_\_\_ DATE: \_\_\_\_\_

ALL DIMENSIONS SHOWN ABOVE ARE FOR REFERENCE ONLY.

## NOTES:

- TORQUE 4X M4-20mm LID SCREWS TO 11lbf-in MINIMUM.
- ENSURE THAT ALL GROMMETS ARE PROPERLY SEATED FOR ENVIRONMENTAL SPECIFICATIONS.

|                             |                  |                                                                                                                                                                                                                      |                  |                |                 |
|-----------------------------|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|----------------|-----------------|
| DRAFTER<br>R. SWART         | DATE<br>12/06/05 | <br>P.O. BOX 9000 MINDEN, NV 89423 TEL: 775-782-2511 FAX: 775-782-4476<br>DWG NO/PART NO/DESCRIPTION<br>IX-3H<br>CUSTOMER PRINT |                  |                |                 |
| MECH ENGINEER<br>R. DUNNING | DATE<br>12/12/05 |                                                                                                                                                                                                                      |                  |                |                 |
| ELEC ENGINEER<br>L. CHANG   | DATE<br>12/07/05 |                                                                                                                                                                                                                      |                  |                |                 |
| MARKETING<br>S. DOTTER      | DATE<br>12/12/05 |                                                                                                                                                                                                                      |                  |                |                 |
| QUALITY DEPT<br>L. JACQUES  | DATE<br>12/09/05 | CAGE CODE<br>61114                                                                                                                                                                                                   | FILE NAME<br>-C1 | SCALE<br>NOTED | SHEET<br>1 OF 1 |