

# HUBER+SUHNER® DATA SHEET

## Between Series Adapter: 31\_MMCX-SMA-50-1/111\_O

Rev.: C



### Description

Adaptor jack/jack  
MMCX jack (female) / SMA jack (female)

Interface standards  
SUHNER-MMCX



### Technical Data

#### Electrical Data

Impedance	50 $\Omega$	
Interface frequency max.	6 GHz	
Frequency range	DC to 2.5 GHz	2.5 to 6 GHz
Return loss	$\geq 26$ dB	$\geq 21$ dB

#### Mechanical Data

Number of matings	500
Weight	0.0043 kg

#### Environmental Data

Operating Temperature	-55 °C to 155 °C
2002/95/EC (RoHS)	compliant

#### Material Data

##### Piece Parts (MMCX)

Centre contact	Copper Beryllium Alloy
Outer contact	Brass
Body	Brass
Insulator	PFA / PTFE

##### Piece Parts (SMA)

Centre contact	Copper Beryllium Alloy
Outer contact	Copper Beryllium Alloy
Body	Copper Beryllium Alloy
Insulator	PFA / PTFE

##### Surface Plating

Gold Plating (Nickel underplated)  
Gold Plating (without Nickel underplating)  
Gold Plating (without Nickel underplating)

##### Surface Plating

Gold Plating (without Nickel underplating)  
Gold Plating (without Nickel underplating)  
Gold Plating (without Nickel underplating)

### Related Documents

Catalogue drawing	DCA-00014596
-------------------	--------------

### Ordering Information

Single package	31_MMCX-SMA-50-1/111_OE
----------------	-------------------------

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**