

HUBER+SUHNER® DATA SHEET

Between Series Adapter: 32_BNC-N-50-51/1--_U

Rev.: D



Description

Adaptor plug/plug
BNC-precision plug (male) / N-precision plug (male)

Interface standards
IEC 60169-8_MIL-STD-348A/404_CECC 22120



Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	4 GHz
VSWR	DC - 4 GHz $\leq 1.05 + 0.01 f$

Mechanical Data

Number of matings	500
Weight	0.0483 kg

Environmental Data

Operating Temperature	°C to °C
2002/95/EC (RoHS)	compliant

Material Data

Piece Parts (BNC-precision)

Centre contact	Brass
Outer contact	Stainless Steel
Body	Stainless Steel
Insulator	PFA / PTFE
Coupling nut	Brass
Gasket	MVQ (Silicone Rubber)

Piece Parts (N-precision)

Centre contact	Copper Beryllium Alloy
Outer contact	Stainless Steel
Body	Stainless Steel
Insulator	Air Dielectric - Bead - PPH
Coupling nut	Brass

Surface Plating

Gold Plating (without Nickel underplating)

SUCOPLATE (R) Plating

Surface Plating

Gold Plating (without Nickel underplating)

SUCOPLATE (R) Plating

Related Documents

Catalogue drawing	DCA-00014558
-------------------	--------------

Ordering Information

Single package	32_BNC-N-50-51/1--_UE
----------------	-----------------------

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions