

# HUBER+SUHNER® DATA SHEET

## Between Series Adapter: 33\_PC35-N-50-1/1--\_U

Rev.: C



### Description

Adaptor plug/jack  
PC 3.5 plug (male) / N-precision jack (female)

Interface standards  
IEC 60169-23

### Technical Data

#### Electrical Data

Impedance	50 $\Omega$	
Interface frequency max.	18 GHz	
Frequency range	DC to 12.4 GHz	12.4 to 18 GHz
Return loss	$\geq 26$ dB	$\geq 23$ dB
Electrical Length	33.52 mm +/- 0.1	

#### Mechanical Data

Number of matings	500
Weight	0.0428 kg

#### Environmental Data

Operating Temperature	-65 °C to 90 °C
2002/95/EC (RoHS)	compliant

#### Material Data

##### Piece Parts (PC 3.5)

Centre contact	Material
Outer contact	Copper Beryllium Alloy
Body	Stainless Steel
Insulator	Stainless Steel
Coupling nut	Air Dielectric - Bead - PPH
Gasket	Bronze
	MVQ (Silicone Rubber)

##### Piece Parts (N-precision)

Centre contact	Material
Outer contact	Copper Beryllium Alloy
Body	Stainless Steel
Insulator	Stainless Steel
	Air Dielectric - Bead - PPH

##### Surface Plating

Gold Plating (without Nickel underplating)

SUCOPLATE (R) Plating

##### Surface Plating

Gold Plating (without Nickel underplating)



### Related Documents

#### Ordering Information

Single package	33_PC35-N-50-1/1--_UE
----------------	-----------------------

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

**HUBER+SUHNER – Excellence in Connectivity Solutions**



**HUBER+SUHNER AG**

**RF Technology**

**9100 Herisau, Switzerland**

Phone +41 (0)71 353 41 11

Fax +41 (0)71 353 45 90

[www.hubersuhner.com](http://www.hubersuhner.com)