

HUBER+SUHNER® DATA SHEET

Between Series Adapter: 33_PC35-QMA-50-1/199_N

Rev.: H



Description

Adaptor plug/jack
PC 3.5 plug (male) / QMA jack (female)

Interface standards
IEC 60169-23 / QMA QLF compliant



Technical Data

Electrical Data

Impedance	50 Ω		
Interface frequency max.	18 GHz		
Frequency range	DC to 1.5 GHz	1.5 to 6 GHz	6 to 18 GHz
Return loss	≥ 35 dB	≥ 30 dB	≥ 20 dB
Electrical Length	25.4 mm +/- 2.6		

Mechanical Data

Number of matings	500
Weight	0.0056 kg

Environmental Data

Operating Temperature	-40 °C to 85 °C
2002/95/EC (RoHS)	compliant

Material Data

Piece Parts (PC 3.5)

Centre contact	Material
Outer contact	Copper Beryllium Alloy
Body	Stainless Steel
Insulator	Stainless Steel
Coupling nut	Air Dielectric - Bead - PS
	Stainless Steel

Surface Plating

SUCOPRO Plating

Passivated (Plating)

Piece Parts (QMA)

Centre contact	Material
Outer contact	Copper Beryllium Alloy
Body	Stainless Steel
Insulator	Stainless Steel
	Air Dielectric - Bead - PS

Surface Plating

SUCOPRO Plating

Related Documents

Outline drawing	DOU-00014034
Catalogue drawing	DCA-00014036

Ordering Information

Single package	33_PC35-QMA-50-1/199_NE
----------------	-------------------------

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG

RF Technology

9100 Herisau, Switzerland

Phone +41 (0)71 353 41 11

Fax +41 (0)71 353 45 90

www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions