

HUBER+SUHNER® DATA SHEET

Between Series Adapter: 34_BNC-QLA-01-1/1--_U

Rev.: B



Description

Bulkhead adaptor jack/jack
BNC jack (female) / QLA-01 jack (female)

Interface standards
IEC 60169-8_MIL-STD-348A/301_CECC 22120



Technical Data

Electrical Data

Impedance other Ω
Interface frequency max. 1.4 GHz

Mechanical Data

Number of matings 500
Weight 0.0092 kg

Environmental Data

Operating Temperature -55 °C to 150 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts (BNC)

| | |
|----------------|------------------------|
| Centre contact | Copper Beryllium Alloy |
| Outer contact | Brass |
| Body | Brass |
| Insulator | PFA / PTFE |

Piece Parts (QLA-01)

| | |
|----------------|------------------------|
| Centre contact | Copper Beryllium Alloy |
| Outer contact | Bronze |
| Body | Brass |
| Insulator | PFA / PTFE |

Surface Plating

Gold Plating (without Nickel underplating)
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating

Surface Plating

Gold Plating (without Nickel underplating)
Gold Plating (Nickel underplated)
SUCOPLATE (R) Plating

Related Documents

Mounting hole DOU-00008762

Ordering Information

Single package 34_BNC-QLA-01-1/1--_UE

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

HUBER+SUHNER – Excellence in Connectivity Solutions



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com