

ADAPTERS, Between Series

BNC (75 Ohm) / Type F, DC - 3 GHz, 75 Ohms

SPECIFICATIONS:

Models: 5070, 5071, 5072, 5073

RoHS
Compliant

Electrical:


Frequency Range _____ DC - 3 GHz
 VSWR _____ 1.30:1 Max.
 Impedance _____ 75 Ohms
 Operating Temp. Range _____ -65°C to +125°C

Mechanical:


Type F Connectors _____ Nickel Plated Brass
 BNC Connectors _____ Nickel Plated Brass
Mates with 75 Ohm BNC Only
 Conductors _____ Gold Plated Beryllium Copper
 and Gold Plated Brass

* K is a Trademark of Anritsu Corp.


Model Number: **5070**
 BNC Male / Type F Male




Model Number: **5071**
 BNC Female / Type F Male



Model Number: **5072**
 BNC Male / Type F Female



Model Number: **5073**
 BNC Female / Type F Female



Note: Dimensions in Brackets are Expressed in Millimeters and are for Reference Only.
 Design, specifications are subject to change without notice. Contact factory for technical specifications before purchasing and/or use.

5070: REV B



Aeroflex / Inmet, Inc. • 300 Dino Drive, Ann Arbor, MI 48103 • U.S.A.
 888-244-6638 or 734-426-5553 • FAX: 734-426-5557
 www.aeroflex-inmet.com • inmet-sales@eroflex.com

