

SUHNER® COAXIAL CONNECTOR DATA SHEET TYPE 31 SMA-50-0-51/199 N

Description

Adaptor jack/jack



General Information

SMA Interface dims acc. to: IEC 60169-15_MIL-STD-348A/310_CECC 22110

Weight: 0.0013 Kg/ 0.05 oz

Electrical Data

Insulator:

 $\begin{array}{ll} \text{Impedance:} & 50\Omega \\ \text{Interface frequency max.:} & 18 \text{ GHz} \\ \end{array}$

Frequency range: 0 ... 2 GHz 2 ... 12 GHz 12 ... 18 VSWR: 1.06 1.11 1.14

Piece Parts Material Surface Plating

PFA / PTFE

Centre contact: Copper Beryllium Alloy Gold Plating (Nickel underplated)
Outer contact: Stainless Steel Passivated (Plating)
Body: Stainless Steel

Attachments Catalogue drawing: DCA-00013743

Order as 31_SMA-50-0-51/199_NE for Single
Order as 31_SMA-50-0-51/199_NH for Bulk 100 pcs

WAIVER

While the information contained in this folder has been carefully compiled to the best of our present knowledge, it is not intended as representation or warranty of any kind on our part regarding the fitness of the products concerned for any particular use or purpose and neither shall any statement contained herein be constructed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The fitness of each product for any particular purpose must be checked beforehand with our specialists.

Issued: 05.12.03 08:26		Document: DOC-0000194326	
RF_Ad_W_PDF	uncontrolled copy	Page 1	



HUBER+SUHNER AG

Mobile Communications + Electronics
CH-9100 Herisau
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
http://www.hubersuhner.com