HUBER+SUHNER® DATA SHEET Within Series Adapter: 34_MCX-75-0-1/111_N

H

Description

Bulkhead adaptor jack/jack MCX-75 jack (female) / MCX-75 jack (female)

Interface standards SUHNER-MCX75

Technical Data

Electrical Data

 $\begin{array}{ll} \text{Impedance} & 75~\Omega \\ \text{Interface frequency max.} & 6~\text{GHz} \end{array}$

Mechanical Data

Number of matings 500 Weight 0.0033 kg

Environmental Data

Operating Temperature °C to °C 2002/95/EC (RoHS) compliant

Material Data

Piece Parts (MCX-75) Material

Centre contact Copper Beryllium Alloy

Outer contact Brass
Body Brass
Insulator PFA / PTFE
Piece Parts (MCX-75) Material

Centre contact Copper Beryllium Alloy

Outer contact Brass
Body Brass
Insulator PFA / PTFE

Related Documents

Mounting hole DOU-00008731

Ordering Information

Single package 34_MCX-75-0-1/111_NE

×

Surface Plating

Gold Plating (Nickel underplated) Gold Plating (Nickel underplated) Gold Plating (Nickel underplated)

Surface Plating

Gold Plating (Nickel underplated) Gold Plating (Nickel underplated) Gold Plating (Nickel underplated)

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

HUBER+SUHNER – Excellence in Connectivity Solutions

H HUBER+SUHNER

HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com