

HUBER+SUHNER® DATA SHEET

Within Series Adapter: 34_QMA-50-0-2/133_N

Rev.: E



Description

Bulkhead adaptor jack/jack
QMA jack (female) / QMA jack (female)

Interface standards
QMA QLF compliant

Technical Data

Electrical Data

Impedance	50 Ω	
Interface frequency max.	18 GHz	
Frequency range	DC to 2.5 GHz	2.5 to 6 GHz
Return loss	≥ 30 dB	≥ 25 dB

Mechanical Data

Number of matings	100
Weight	0.0075 kg

Environmental Data

Operating Temperature	-40 °C to 85 °C
2002/95/EC (RoHS)	compliant

Material Data

Piece Parts (QMA)

Centre contact	Material Copper Beryllium / Bronze
Outer contact	Brass
Body	Brass
Insulator	PTFE (ELCA)
Gasket	MVQ

Surface Plating

SUCOPRO Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating

Piece Parts (QMA)

Centre contact	Material Copper Beryllium / Bronze
Outer contact	Brass
Body	Brass
Insulator	PTFE (ELCA)
Gasket	MVQ

Surface Plating

SUCOPRO Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating

Related Documents

Outline drawing	DOU-00067384
Mounting hole	DOU-00008860

Ordering Information

Single package	34_QMA-50-0-2/133_NE
----------------	----------------------

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions