

HUBER+SUHNER® DATA SHEET

Within Series Adapter: 34_SHV-50-0-3/100_N

Rev.: D



Description

Bulkhead adaptor jack/jack
SHV jack (female) / SHV jack (female)

Interface standards
IEC 60498_MIL-STD-348A/314



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 0.3 GHz

Mechanical Data

Number of matings 500
Weight 0.0419 kg

Environmental Data

Operating Temperature -65 °C to 165 °C
2002/95/EC (RoHS) not compliant

Material Data

Piece Parts (SHV)

| | |
|----------------|------------|
| Centre contact | Brass |
| Outer contact | Brass |
| Body | Brass |
| Insulator | PFA / PTFE |
| Gasket | FPM |

Piece Parts (SHV)

| | |
|----------------|------------|
| Centre contact | Brass |
| Outer contact | Brass |
| Body | Brass |
| Insulator | PFA / PTFE |
| Gasket | FPM |

Surface Plating

Gold Plating (Nickel underplated)
Silver Plating
Silver Plating

Surface Plating

Gold Plating (Nickel underplated)
Silver Plating
Silver Plating

Related Documents

Outline drawing DOU-00013636
Mounting hole DOU-00008751

Ordering Information

Single package 34_SHV-50-0-3/100_NE

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

HUBER+SUHNER – Excellence in Connectivity Solutions



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com