

HUBER+SUHNER® DATA SHEET

Within Series Adapter: 34_SMB-50-0-3/111_N

Rev.: B



Description

Bulkhead adaptor jack/jack
SMB jack (female) / SMB jack (female)

Interface standards
IEC 60169-10_MIL-STD-348A/311_CECC 22130



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 4 GHz

Mechanical Data

Number of matings 500
Weight 0.0022 kg

Environmental Data

Operating Temperature -65 °C to 165 °C
2002/95/EC (RoHS) not compliant

Material Data

Piece Parts (SMB)

Centre contact	Brass
Outer contact	Brass
Body	Brass
Insulator	PFA / PTFE
Gasket	NR (Natural Rubber)

Piece Parts (SMB)

Centre contact	Brass
Outer contact	Brass
Body	Brass
Insulator	PFA / PTFE
Gasket	NR (Natural Rubber)

Surface Plating

Gold Plating (without Nickel underplating)
Gold Plating (Nickel underplated)
Gold Plating (Nickel underplated)

Surface Plating

Gold Plating (without Nickel underplating)
Gold Plating (Nickel underplated)
Gold Plating (Nickel underplated)

Related Documents

Outline drawing DOU-00013566
Mounting hole DOU-00008855

Ordering Information

Single package 34_SMB-50-0-3/111_NE

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions