

HUBER+SUHNER® DATA SHEET

Within Series Adapter: 43_QLA-01-0-1/112_N



Description

T-adaptor, 2 jacks, 1 plug
QLA-01 jack (female) / QLA-01 plug (male)

Interface standards
NIM-CAMAC-Standard CD/N549



Technical Data

Electrical Data

Impedance other Ω
Interface frequency max. 1.4 GHz

Mechanical Data

Number of matings 10000
Weight 0.0071 kg

Environmental Data

Operating Temperature -55 °C to 150 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts (QLA-01)

| | |
|----------------|--------------------------|
| Centre contact | Copper Beryllium / Brass |
| Outer contact | |
| Body | Brass |
| Insulator | PFA / PTFE |

Piece Parts (QLA-01)

| | |
|----------------|--------------------------|
| Centre contact | Copper Beryllium / Brass |
| Outer contact | |
| Body | Brass |
| Insulator | PFA / PTFE |
| Coupling nut | Brass |

Surface Plating

Gold Plating (Nickel underplated)
Gold Plating (Nickel underplated)
Nickel Plating

Surface Plating

Gold Plating (Nickel underplated)
Gold Plating (Nickel underplated)
Nickel Plating

Nickel Plating

Related Documents

Ordering Information

Single package 43_QLA-01-0-1/112_NE

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions