	8	7	6	5	4		3		2	I	1	
	This document, including the design, configuration and mechanical feath revealed herein are the sole, confidential and proprietary property of							REV.	DESCRIPTION	DATE	APPROVED	
	TRU Corporation. Reproduction or use thereof, in whole or part, is prohibit without the prior written consent of TRU Corporation.	ed					_	-	ORIGINAL ISSUE	12/15/11	AM	
								A	CHANGE PER ECO-4212	05/29/12	TRC	
D				TRU-160 mfd YY								
		ES: 3.5mm(m) G, STRAIGHT	SHRINK SLEEVE			SF	IRINK SLEEV	/E	SERIES: 3.5mm(m) PLUG, STRAIGHT			
С				CABLE, 1 36 IN ±	0.25 IN					_		
-		(3.22	2) — — — —	(3 (REFERENC			9	(3.22)			•
В												
	NOTES: 1. UNLESS OTHERWISE SPECI DIMENSIONS ARE REFEREN	NCE ONLY.		MATERIAL		DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES	DRAWN MVC ENG APPR. AM	DATE 12/06/11 DATE 12/06/11	EXPERIENCE. THU INNOVATION.	TRU Corpora 245 Lynnfield Peabody, MA	tion St, 01960	
A	2. ELECTRICAL SPECIFICATIONS: FREQUENCY RANGE: .05 TO 18 GHz VSWR MAX: 1.35:1				TOLERANCES: FRACTIONS: ±1/64 .XX : ±.01 .XXX: ±.005 ANGLES: ±1/2	MFG APPR.	DATE	TITLE: CABLE ASSEMBLY TRUtest18-3.5m-3.5m-3.0)	,	
	INSERTION LOSS: MAX	INSERTION LOSS: MAX: 1.60 dB		COMMENTS:	unginabet like	MACHINED SURFACES:	THIRD ANGLE PR		SIZE DWG. NO. TRU CAGE CODE: 92180	J-16001-03 SCALE: 1:1	REV A SHEET 1 OF 1	
	8	8 7 6			surface area: sq inch weight: lbs		3		2	JUALE: 1:1		
	-		-	-	·		-		_		-	



С





