

Stainless Steel “M” Series

3/4" hole; 1-1/8" - 18 thread; installs from above

Model	Length of Coax	Coax	Connector	Type
SM34	None	N/A	None	N/A
SM-NC	17'	RG-58A/U	None	N/A
SMC-NC	17'	RG-58/U	None	N/A
SMML195-NC	17'	Pro-Flex™ Plus 195	None	N/A
SMFLC-NC	17'	RG-58 Teflon	None	N/A
SM	17'	RG-58A/U	PL259	Solder
SMCP	17'	RG-58A/U	PL259	Crimp
SMSP	14'	RG-58A/U	PL259	Solder
SMPCP	17'	RG-58/U	PL259	Crimp
SMP	17'	RG-58/U	Teflon PL259	Solder
SMML195P	17'	Pro-Flex™ Plus 195	Teflon PL259	Solder
SMPL	17'	RG-58/U	Mini-UHF	Crimp
SMML195PL	17'	Pro-Flex™ Plus 195	Mini-UHF	Crimp
SMML195RPC	17'	Pro-Flex™ Plus 195	Reverse Polarity TNC	Crimp
SMML195C	17'	Pro-Flex™ Plus 195	TNC	Crimp
SMC	17'	RG-58/U	TNC	Crimp
SMBN	17'	RG-58/U	BNC	Crimp
SMML195BN	17'	Pro-Flex™ Plus 195	BNC	Crimp
SMML195NCP	17'	Pro-Flex™ Plus 195	N	Crimp
SMML195MSMA	17'	Pro-Flex™ Plus 195	Male SMA	Crimp



SM

Connectors are shipped loose. Connectors may be attached upon request for an additional charge.