




# SMA 50 Ohm Right Angle Jack Receptacle - Surface Mount



| VSWR & FREQ. RANGE    | GOLD PLATED  | NICKEL PLATED  | PACKAGING                        |
|-----------------------|--------------|----------------|----------------------------------|
| VSWR: N/A<br>0-18 GHz | 142-0711-301 | 142-0711-305 △ | STOCK                            |
|                       | 142-0711-302 | 142-0711-306 △ | TAPE & REEL<br>425 pcs. per reel |

△ Connector Mounting Rails  
60%/40% Tin/Lead Coated  
(Solder Plated)

## Recommended Land Pattern



# SMA - 50 Ohm Connectors

## Specifications

## ELECTRICAL RATINGS

**Impedance:** 50 ohms

**Frequency Range:**

|                                                                                |            |
|--------------------------------------------------------------------------------|------------|
| Dummy loads .....                                                              | 0-2 GHz    |
| Flexible cable connectors .....                                                | 0-12.4 GHz |
| Uncabled receptacles, RA semi-rigid and adapters .....                         | 0-18.0 GHz |
| Straight semi-rigid cable connectors and<br>field replaceable connectors ..... | 0-26.5 GHz |

**VSWR:** (f = GHz)

|                                     | Straight<br>Cabled Connectors | Right Angle<br>Cabled Connectors |
|-------------------------------------|-------------------------------|----------------------------------|
| RG-178 cable .....                  | 1.20 + .025f                  | 1.20 + .03f                      |
| RG-316, LMR-100 cable .....         | 1.15 + .02f                   | 1.15 + .03f                      |
| RG-58, LMR-195 cable .....          | 1.15 + .01f                   | 1.15 + .02f                      |
| RG-142 cable .....                  | 1.15 + .01f                   | 1.15 + .02f                      |
| LMR-200, LMR-240 cable .....        | 1.10 + .03f                   | 1.10 + .06f                      |
| .086 semi-rigid .....               | 1.07 + .008f                  | 1.18 + .015f                     |
| .141 semi-rigid (w/contact) .....   | 1.05 + .008f                  | 1.15 + .015f                     |
| .141 semi-rigid (w/o contact) ..... | 1.035 + .005f                 |                                  |

Jack-bulkhead jack adapter and plug-plug adapter .....

Jack-jack adapter and plug-jack adapter .....

Uncabled receptacles, dummy loads .....

Field replaceable (see page 59) .....

**Working Voltage:** (Vrms maximum)\*

**Connectors for Cable Type**      **Sea Level**   **70K Feet**

|                                                                                                   |     |     |
|---------------------------------------------------------------------------------------------------|-----|-----|
| RG-178 .....                                                                                      | 170 | 45  |
| RG-316; LMR-100, 195, 200 .....                                                                   | 250 | 65  |
| RG-58, RG-142, LMR-240, .086 semi-rigid,<br>uncabled receptacles, .141 semi-rigid w/o contact ... | 335 | 85  |
| .141 semi-rigid with contact and adapters .....                                                   | 500 | 125 |
| Dummy loads .....                                                                                 | N/A |     |

**Dielectric Withstanding Voltage:** (VRMS minimum at sea level)\*

|                                                                                                          |      |
|----------------------------------------------------------------------------------------------------------|------|
| Connectors for RG-178 .....                                                                              | 500  |
| Connectors for RG-316; LMR-100, 195, 200 .....                                                           | 750  |
| Connectors for RG-58, RG-142, LMR-240, .086 semi-rigid,<br>field replaceable, uncabled receptacles ..... | 1000 |
| Connectors for .141 semi-rigid with contact and adapters .....                                           | 1500 |
| Connectors for .141 semi-rigid w/o contact, dummy loads .....                                            | N/A  |

**Corona Level:** (Volts minimum at 70,000 feet)\*

|                                                                                                                    |     |
|--------------------------------------------------------------------------------------------------------------------|-----|
| Connectors for RG-178 .....                                                                                        | 125 |
| Connectors for RG-316; LMR-100, 195, 200 .....                                                                     | 190 |
| Connectors for RG-58, RG-142, LMR-240, .086 semi-rigid,<br>uncabled receptacles, .141 semi-rigid w/o contact ..... | 250 |
| Connectors for .141 semi-rigid with contact and adapters .....                                                     | 375 |
| Dummy loads .....                                                                                                  | N/A |

**Insertion Loss:** (dB maximum)

|                                                            |      |                                    |
|------------------------------------------------------------|------|------------------------------------|
| Straight flexible cable connectors<br>and adapters .....   | 0.06 | $\sqrt{f}$ (GHz), tested at 6 GHz  |
| Right angle flexible cable<br>connectors .....             | 0.15 | $\sqrt{f}$ (GHz), tested at 6 GHz  |
| Straight semi-rigid cable<br>connectors with contact ..... | 0.03 | $\sqrt{f}$ (GHz), tested at 10 GHz |
| Right angle semi-rigid cable<br>connectors .....           | 0.05 | $\sqrt{f}$ (GHz), tested at 10 GHz |
| Straight semi-rigid cable<br>connectors w/o contact .....  | 0.03 | $\sqrt{f}$ (GHz), tested at 16 GHz |
| Straight low loss flexible<br>cable connectors .....       | 0.06 | $\sqrt{f}$ (GHz), tested at 1 GHz  |
| Right Angle low loss flexible<br>cable connectors .....    | 0.15 | $\sqrt{f}$ (GHz), tested at 1 GHz  |
| Uncabled receptacles, field replaceable, dummy loads ..... |      | N/A                                |

**Insulation Resistance:** 5000 megohms minimum

**Contact Resistance:** (milliohms maximum)   **Initial**   **After Environmental**

|                                                                               |      |      |
|-------------------------------------------------------------------------------|------|------|
| Center contact (straight cabled connectors<br>and uncabled receptacles) ..... | 3.0* | 4.0* |
| Center contact (right angle cabled<br>connectors and adapters) .....          | 4.0  | 6.0  |
| Field replaceable connectors .....                                            | 6.0  | 8.0  |
| Outer contact (all connectors) .....                                          | 2.0  | N/A  |
| Braid to body (gold plated connectors) .....                                  | 0.5  | N/A  |
| Braid to body (nickel plated connectors) .....                                | 5.0  | N/A  |

\*N/A where the cable center conductor is used as a contact

**RF Leakage:** (dB minimum, tested at 2.5 GHz)

|                                                                                                                        |        |
|------------------------------------------------------------------------------------------------------------------------|--------|
| Flexible cable connectors, adapters and .141 semi-rigid<br>connectors w/o contact .....                                | -60 dB |
| Field replaceable w/o EMI gasket .....                                                                                 | -70 dB |
| .086 semi-rigid connectors and .141 semi-rigid connectors<br>with contact, and field replaceable with EMI Gasket ..... | -90 dB |
| Two-way adapters .....                                                                                                 | -90 dB |
| Uncabled receptacles, dummy loads .....                                                                                | N/A    |

**RF High Potential Withstanding Voltage:** (Vrms minimum, tested at 4 and 7 MHz)\*

|                                                                                                                          |      |
|--------------------------------------------------------------------------------------------------------------------------|------|
| Connectors for RG-178 .....                                                                                              | 335  |
| Connectors for RG-316; LMR-100, 195, 200 .....                                                                           | 500  |
| Connectors for RG-58, RG-142, LMR-240, .086 semi-rigid,<br>.141 semi-rigid cable w/o contact, uncabled receptacles ..... | 670  |
| Connectors for .141 semi-rigid with contact and adapters .....                                                           | 1000 |

**Power Rating (Dummy Load):** 0.5 watt @ + 25°C, derated to 0.25 watt @ +125°C

## MECHANICAL RATINGS

**Engagement Design:** MIL-C-39012, Series SMA

**Engagement/Disengagement Force:** 2 inch-pounds maximum

**Mating Torque:** 7 to 10 inch-pounds

**Bulkhead Mounting Nut Torque:** 15 inch-pounds

**Coupling Proof Torque:** 15 inch-pounds minimum

**Coupling Nut Retention:** 60 pounds minimum

**Contact Retention:**

6 lbs. minimum axial force (captivated contacts)

4 inch-ounce minimum torque (uncabled receptacles)

**Cable Retention:**      **Axial Force\*(lbs)**   **Torque (in-oz)**

|                                      |    |     |
|--------------------------------------|----|-----|
| Connectors for RG-178 .....          | 10 | N/A |
| Connectors for RG-316, LMR-100 ..... | 20 | N/A |
| Connectors for LMR-195, 200 .....    | 30 | N/A |
| Connectors for RG-58, LMR-240 .....  | 40 | N/A |
| Connectors for RG-142 .....          | 45 | N/A |
| Connectors for .086 semi-rigid ..... | 30 | 16  |
| Connectors for .141 semi-rigid ..... | 60 | 55  |

\*Or cable breaking strength whichever is less.

**Durability:** 500 cycles minimum

100 cycles minimum for .141 semi-rigid connectors w/o contact

**ENVIRONMENTAL RATINGS** (Meets or exceed the applicable paragraph of MIL-C-39012)

**Temperature Range:** - 65°C to + 165°C

**Thermal Shock:** MIL-STD-202, Method 107, Condition B

**Corrosion:** MIL-STD-202, Method 101, Condition B

**Shock:** MIL-STD-202, Method 213, Condition I

**Vibration:** MIL-STD-202, Method 204, Condition D

**Moisture Resistance:** MIL-STD-202, Method 106

†Avoid user injury due to misapplication. See safety advisory definitions inside front cover.

# SMA - 50 Ohm Connectors

## Specifications

## MATERIAL SPECIFICATIONS

**Bodies:** Brass per QQ-B-626, gold plated\* per MIL-G-45204 .00001" min. or nickel plated per QQ-N-290

**Contacts:** Male - brass per QQ-B-626, gold plated per MIL-G-45204 .00003" min.

Female - beryllium copper per QQ-C-530, gold plated per MIL-G-45204 .00003" min.

**Nut Retention Spring:** Beryllium copper per QQ-C-533. Unplated

**Insulators:** PTFE fluorocarbon per ASTM D 1710 and ASTM D 1457 or Tefzel per ASTM D 3159 or PFA 340 per ASTM

**Expansion Caps:** Brass per QQ-B-613, gold plated per MIL-G-45204 .00001" min. or nickel plated per QQ-N-290

**Crimp Sleeves:** Copper per WW-T-799 or brass per QQ-B-613, gold plated per MIL-G-45204 .00001" min. or nickel plated per QQ-N-290



**Mounting Hardware:** Brass per QQ-B-626 or QQ-B-613, gold plated per MIL-G-45204 .00001" min. or nickel plated per QQ-N-290

**Seal Rings:** Silicone rubber per ZZ-R-765

**EMI Gaskets:** Conductive silicone rubber per MIL-G-83528, Type M

\* All gold plated parts include a .00005" min. nickel underplate barrier layer.

### Mating Engagement for SMA Series per MIL-C-39012



#### NOTES

1. ID OF CONTACT TO MEET VSWR, CONTACT RESISTANCE AND INSERTION WITHDRAWAL FORCES WHEN MATED WITH DIA .0355-.0370 MALE PIN.