

HUBER+SUHNER® DATA SHEET

Coaxial PCB Connector: 81_MMBX-50-0-11/111_N

Rev.: E



Description

Straight PCB plug

Interface Standards
SUHNER-MMBX



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 12.4 GHz

Mechanical Data

Board mounting type through holes
Weight 0.0023 kg

Environmental Data

Operating Temperature -55 °C to 155 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

Centre contact
Outer contact
Body
Insulator

Material

Copper Beryllium Alloy
Bronze
Brass
PTFE / LCP

Surface Plating

Gold Plating (Nickel underplated)
SUCOPRO Plating
SUCOPRO Plating

Related Documents

Outline drawing DOU-00013259
Catalogue drawing DCA-00013261
Mounting hole DOU-00002008

Ordering Information

Tape and Reel package 81_MMBX-50-0-11/111_NM
Bulk 100 pcs package 81_MMBX-50-0-11/111_NH

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions