HUBER+SUHNER® DATA SHEET Coaxial PCB Connector: 82 SMB-S50-0-18/111 N



Description

Straight PCB jack

Technical Data

Interface Standards IEC 60169-10 MIL-STD-348A/311 CECC 22130



Electrical Data 50 Ω Impedance Interface frequency max. 4 GHz **Mechanical Data** Board mounting type surface mount Weight 0.006 kg **Environmental Data Operating Temperature** -65 °C to 165 °C 2002/95/EC (RoHS) compliant **Material Data Piece Parts** Material Surface Plating Gold Plating (Nickel underplated) Centre contact Brass Outer contact SUCOPRO Plating Brass Body Brass SUCOPRO Plating Insulator PFA / PTFE **Related Documents** Outline drawing DOU-00013274 Catalogue drawing DCA-00013276 Mounting hole DOU-00012611 Ordering Information Bulk 100 pcs package 82_SMB-S50-0-18/111_NH

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVERI

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

HUBER+SUHNER – Excellence in Connectivity Solutions

Fax

HUBER+SUHNER

HUBER+SUHNER AG **RF** Technology

www.hubersuhner.com

9100 Herisau, Switzerland

Phone +41 (0)71 353 41 11 +41 (0)71 353 45 90