

# HUBER+SUHNER® DATA SHEET

## Coaxial PCB Connector: 84\_SMC-50-0-4/111\_T

Rev.: D



### Description

Right angle PCB plug

Interface Standards

IEC 60169-9\_MIL-STD-348A/312\_CECC 22140

### Technical Data

#### Electrical Data

Impedance 50  $\Omega$   
Interface frequency max. 10 GHz

#### Mechanical Data

Board mounting type through holes  
Weight 0.0035 kg

#### Environmental Data

Operating Temperature -65 °C to 165 °C  
2002/95/EC (RoHS) compliant

#### Material Data

##### Piece Parts

Centre contact	Copper Beryllium Alloy
Outer contact	Brass
Body	Brass
Insulator	PTFE
Coupling nut	Brass

##### Surface Plating

Gold Plating (without Nickel underplating)
Gold Plating (without Nickel underplating)
Gold Plating (without Nickel underplating)
Gold Plating (without Nickel underplating)

### Related Documents

Outline drawing DOU-00013125

### Ordering Information

Single package 84\_SMC-50-0-4/111\_TE

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
**RF Technology**  
**9100 Herisau, Switzerland**  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
[www.hubersuhner.com](http://www.hubersuhner.com)

**HUBER+SUHNER – Excellence in Connectivity Solutions**