## HUBER+SUHNER® DATA SHEET Coaxial PCB Connector: 85 QMA-S50-0-2/111 N



## Description

Right angle PCB jack

Interface Standards QMA QLF compliant



## **Technical Data**

## **Electrical Data**

 $\begin{array}{ll} \mbox{Impedance} & \mbox{50} \ \Omega \\ \mbox{Interface frequency max.} & \mbox{18 GHz} \end{array}$ 

**Mechanical Data** 

Board mounting type surface mount Weight 0.0064 kg

**Environmental Data** 

Operating Temperature -40 °C to 85 °C 2002/95/EC (RoHS) compliant

**Material Data** 

Piece PartsMaterialCentre contactCopper Beryllium / BronzeOuter contactBrassPadyPress

Body Brass
Insulator PFA / PTFE

**Related Documents** 

Outline drawing DOU-00012592 Mounting hole DOU-00013090

**Ordering Information** 

 Bulk 100 pcs package
 85\_QMA-S50-0-2/111\_NH

 Single package
 85\_QMA-S50-0-2/111\_NE

 Tape and Reel package
 85\_QMA-S50-0-2/111\_NM

Surface Plating

SUCOPRO Plating SUCOPRO Plating SUCOPRO Plating

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

**HUBER+SUHNER – Excellence in Connectivity Solutions** 

H HUBER+SUHNER

HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90

www.hubersuhner.com

Document: DOC-0000192654 I Issued: 06.11.07 Uncontrolled Copy Page 1/1