

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 11_MMPX-50-2-2/111_N

Rev.: M



Description

Straight cable plug

Interface Standards



Technical Data

Electrical Data

Impedance	50 Ω		
Interface frequency max.	65 GHz		
Frequency range	DC to 26.5 GHz	26.5 to 50	
GHz	50 to 65 GHz		
Return loss	≥ 25 dB	≥ 17.5 dB	≥ 17.5 dB

Mechanical Data

Centre contact	plugged
Outer contact	soldered

Environmental Data

Operating Temperature	-65 °C to 155 °C
2002/95/EC (RoHS)	compliant

Material Data

Piece Parts

Centre contact
Outer contact
Body
Insulator

Material

Copper Beryllium / Brass
Brass / Messing
Brass / Messing
PTFE

Surface Plating

SUCOPRO / Gold Plating
SUCOPRO / Gold Plating
SUCOPRO / Gold Plating

Related Documents

Outline drawing	DOU-00063967
-----------------	--------------

Ordering Information

package	
Single package	11_MMPX-50-2-2/111_NE

Additional Information

Suitable cables	EZ_86_TP_M17, EZ_86_AL_TP_M17, SUCOFORM_86, MULTIFLEX_86
-----------------	--

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER

HUBER+SUHNER AG

RF Technology

9100 Herisau, Switzerland

Phone +41 (0)71 353 41 11

Fax +41 (0)71 353 45 90

www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions