# **HUBER+SUHNER® DATA SHEET**Coaxial Cable Connector: 11 N-50-7-33/133 N



## Description

Straight cable plug

Interface Standards IEC 61169-16\_MIL-STD-348A/304\_CECC 22210



#### **Technical Data**

#### **Electrical Data**

 $\begin{array}{ll} \text{Impedance} & \quad 50~\Omega \\ \text{Interface frequency max.} & \quad 11~\text{GHz} \end{array}$ 

#### **Mechanical Data**

Centre contact crimped
Outer contact crimped
Weight 0.0376 kg

#### **Environmental Data**

Operating Temperature -65 °C to 165 °C 2002/95/EC (RoHS) compliant

#### **Material Data**

Piece PartsMaterialCentre contactBrassOuter contactBrassBodyBrassInsulatorPFA / PTFECoupling nutBrass

Gasket MVQ (Silicone Rubber)

Crimp ferrule Copper

### **Related Documents**

Outline drawing DOU-00007848
Catalogue drawing DOU-00006943
Assembly instruction DOC-0000179346

## **Ordering Information**

Single package 11\_N-50-7-33/133\_NE

## **Additional Information**

Suitable cable S 07232

**Surface Plating** 

Gold Plating (Nickel underplated) SUCOPLATE (R) Plating SUCOPLATE (R) Plating

SUCOPLATE (R) Plating

SUCOPLATE (R) Plating

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

**HUBER+SUHNER – Excellence in Connectivity Solutions** 

H HUBER+SUHNER

HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

Document: DOC-0000183076 J Issued: 01.11.07 Uncontrolled Copy Page 1/1