

# HUBER+SUHNER® DATA SHEET

## Coaxial Cable Connector: 11\_PC35-50-3-4/199\_U



### Description

Straight cable plug for flexible cable

Interface Standards  
IEC 60169-23

### Technical Data

#### Electrical Data

Impedance 50  $\Omega$   
Interface frequency max. 33 GHz

#### Mechanical Data

Centre contact plugged  
Outer contact soldered  
Weight 0.0057 kg

#### Environmental Data

Operating Temperature -65 °C to 90 °C  
2002/95/EC (RoHS) compliant

#### Material Data

##### Piece Parts

Centre contact	Copper Beryllium Alloy
Outer contact	Stainless Steel
Body	Stainless Steel
Insulator	PS
Coupling nut	Stainless Steel
Gasket	MVQ (Silicone Rubber)

##### Surface Plating

Gold Plating (without Nickel underplating)

#### Related Documents

Outline drawing	DOU-00064428
Catalogue drawing	DCA-00089646
Assembly instruction	DOC-0000215467

#### Ordering Information

package 11\_PC35-50-3-4/199\_UE

#### Additional Information

Suitable cables EZ\_141\_TP\_M17, EZ\_141\_AL\_TP\_M17, SUCOFORM\_141, MULTIFLEX\_141

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

**HUBER+SUHNER – Excellence in Connectivity Solutions**



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com