

Coaxial Cable Connector 11_QMA-W50-2-8/133_N

Description

Straight cable plug

Interface standards

QMA IP 68 rated - QLF compliant



Technical Data

Electrical Data

| | |
|--------------------------|-------------|
| Impedance | 50 Ω |
| Interface frequency max. | 18 GHz |

Mechanical Data

| | |
|----------------|-----------|
| Centre contact | soldered |
| Outer 2contact | crimped |
| Weight | 0.0047 kg |

Environmental Data

| | |
|-----------------------|------------------|
| Operating temperature | -40 °C to 105 °C |
| 2011/65/EU (RoHS) | compliant |

Material Data

| Piece Parts | Material | Surface Plating |
|----------------|--------------------------------|-----------------------|
| Centre contact | Brass | SUCOPRO Plating |
| Outer contact | Brass | SUCOPLATE (R) Plating |
| Body | Brass | SUCOPLATE (R) Plating |
| Insulator | PTFE (Polytetrafluoroethylene) | |
| Gasket | VMQ (Silicone rubber) | |
| Crimp ferrule | Copper | |

Related Documents

| | |
|----------------------|----------------|
| Outline drawing | DOU-00119158 |
| Catalogue drawing | DCA-00200073 |
| Assembly instruction | DOC-0000312675 |

Ordering Information

| | |
|----------------------|-----------------------|
| Bulk 100 pcs package | 11_QMA-W50-2-8/133_NH |
|----------------------|-----------------------|

Additional Information

| | |
|-----------------|--------------------------------------|
| Suitable cables | ENVIROFLEX_316, RG_174_/U, RG_316_/U |
|-----------------|--------------------------------------|