

# HUBER+SUHNER® DATA SHEET

## Coaxial Cable Connector: 11\_SHV-50-3-1/133\_N



### Description

Straight cable plug

Interface Standards

IEC 60498\_MIL-STD-348A/314



### Technical Data

#### Electrical Data

Impedance 50  $\Omega$   
Interface frequency max. 0.3 GHz

#### Mechanical Data

Centre contact crimped  
Outer contact crimped  
Weight 0.0186 kg

#### Environmental Data

Operating Temperature -65 °C to 165 °C  
2002/95/EC (RoHS) compliant

#### Material Data

##### Piece Parts

Centre contact	Copper Beryllium Alloy
Outer contact	Copper Beryllium Alloy
Body	Brass
Insulator	PFA / PTFE
Coupling nut	Brass
Gasket	MVQ (Silicone Rubber)
Crimp ferrule	Copper

##### Surface Plating

Gold Plating (Nickel underplated)
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating

#### Related Documents

Outline drawing	DOU-00008330
Catalogue drawing	DOU-00006112
Assembly instruction	DOC-0000179317

#### Ordering Information

Single package 11\_SHV-50-3-1/133\_NE

#### Additional Information

Suitable cables RG\_58\_C/U, G\_03232, GX\_03272

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

**HUBER+SUHNER – Excellence in Connectivity Solutions**



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com