

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 11_SMA-50-5-2/199_N

Rev.: E



Description

Straight cable plug

Interface Standards

IEC 60169-15_MIL-STD-348A/310_CECC 22110



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 18 GHz

Mechanical Data

Centre contact soldered
Outer contact clamped
Weight 0.0089 kg

Environmental Data

Operating Temperature -65 °C to 165 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts	Material
Centre contact	Copper Beryllium Alloy
Outer contact	Stainless Steel
Body	Stainless Steel
Insulator	PFA / PTFE
Coupling nut	Stainless Steel
Gasket	MVQ (Silicone Rubber)

Surface Plating

Gold Plating (without Nickel underplating)

Related Documents

Catalogue drawing DOU-00008080
Assembly instruction DOC-0000181417

Ordering Information

Single package 11_SMA-50-5-2/199_NE

Additional Information

Suitable cable EZ_250_TP_M17

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions