

# HUBER+SUHNER® DATA SHEET

## Coaxial Cable Connector: 11\_TNC-50-3-5/133\_N

Rev.: B



### Description

Straight cable plug

Interface Standards

IEC 60169-17\_MIL-STD-348A/313\_CECC 22200



### Technical Data

#### Electrical Data

Impedance 50  $\Omega$   
Interface frequency max. 11 GHz

#### Mechanical Data

Centre contact soldered  
Outer contact clamped  
Weight 0.0196 kg

#### Environmental Data

Operating Temperature -65 °C to 165 °C  
2002/95/EC (RoHS) compliant

#### Material Data

Piece Parts	Material
Centre contact	Brass
Outer contact	Brass
Body	Brass
Insulator	PFA / PTFE
Coupling nut	Brass
Gasket	MVQ (Silicone Rubber)

#### Surface Plating

Gold Plating (Nickel underplated)  
SUCOPLATE (R) Plating  
SUCOPLATE (R) Plating

### Related Documents

Outline drawing DOU-00006494  
Catalogue drawing DOU-00006059  
Assembly instruction DOC-0000179064

### Ordering Information

Single package 11\_TNC-50-3-5/133\_NE  
Bulk 100 pcs package 11\_TNC-50-3-5/133\_NH

### Additional Information

Suitable cables RG\_58\_C/U, RG\_223\_U, ENVIROFLEX\_142, RG 400 /U

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

**HUBER+SUHNER – Excellence in Connectivity Solutions**



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com