

## Coaxial Cable Connector 14\_BMA-50-3-32/133\_N

### Description

Straight bulkhead cable plug

Interface standards

BMA Economic (mech. compatible with BMA Std acc. to Mil)



### Technical Data

#### Electrical Data

Impedance	50 $\Omega$
Interface frequency max.	12.4 GHz

#### Mechanical Data

Centre contact	soldered
Outer 2contact	crimped

#### Environmental Data

Operating temperature	-40 °C to 125 °C
2011/65/EU (RoHS)	compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium / Brass	SUCOPRO Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PTFE (Polytetrafluoroethylene)	
Fastening nut	Brass	
Washer	Bronze	
Crimp ferrule	Copper	

### Related Documents

Outline drawing	DOU-00230460
Catalogue drawing	DCA-00238082
Assembly instruction	DOC-0000408386
Mounting hole	DOU-00008972

### Ordering Information

Bulk 100 pcs package	14_BMA-50-3-32/133_NH
----------------------	-----------------------

### Additional Information

Suitable cables	RG_223_/U, RG_400_/U, RG_142_B/U
-----------------	----------------------------------