

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 14_BMA-50-3-31/133_N

Rev.: E.00



Description

Straight bulkhead cable plug

Interface Standards

BMA Economic (mech. compatible with BMA Std acc. to Mil)

Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 12.4 GHz

Mechanical Data

Centre contact plugged
Outer contact soldered

Environmental Data

Operating Temperature -40 °C to 125 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

Centre contact
Outer contact
Body
Insulator
Gasket
Fastening nut
Washer

Material

Copper Beryllium Alloy
Brass
Brass
PTFE (Polytetrafluoroethylene)
EPDM (Ethylene propylene diene rubber)
Brass
Bronze

Surface Plating

SUCOPRO Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating

Related Documents

Outline drawing DOU-00230309
Catalogue drawing DCA-00238080
Assembly instruction DOC-0000408218
Mounting hole DOU-00008972

Ordering Information

Bulk 100 pcs package 14_BMA-50-3-31/133_NH

Additional Information

Suitable cables EZ_141_TP_M17, SUCOFORM_141, MULTIFLEX_141



HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions