

# HUBER+SUHNER® DATA SHEET

## Coaxial Cable Connector: 16\_MMBX-50-2-2/111\_N

Rev.: D



### Description

Right angle cable plug

Interface Standards  
SUHNER-MMBX



### Technical Data

#### Electrical Data

Impedance 50  $\Omega$   
Interface frequency max. 12.4 GHz

#### Mechanical Data

Centre contact soldered  
Outer contact crimped  
Weight 0.0011 kg

#### Environmental Data

Operating Temperature -55 °C to 155 °C  
2002/95/EC (RoHS) compliant

#### Material Data

##### Piece Parts

Centre contact Copper Beryllium Alloy  
Outer contact Copper Beryllium Alloy  
Body Brass  
Insulator PFA / PTFE  
Crimp ferrule Copper

##### Surface Plating

Gold Plating (Nickel underplated)  
SUCOPRO Plating  
SUCOPRO Plating  
Gold Plating (without Nickel underplating)

### Related Documents

Outline drawing DOU-00006252  
Catalogue drawing DOU-00006254  
Assembly instruction DOC-0000178673

### Ordering Information

Single package 16\_MMBX-50-2-2/111\_NE  
Bulk 100 pcs package 16\_MMBX-50-2-2/111\_NH

### Additional Information

Suitable cables ENVIROFLEX\_316\_D, K\_02252\_D, G\_02232\_D

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

**HUBER+SUHNER – Excellence in Connectivity Solutions**



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com