

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 16_N-50-7-26/133_N

Rev.: D



Description

Right angle cable plug

Interface Standards

IEC 61169-16_MIL-STD-348A/304_CECC 22210



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 11 GHz

Mechanical Data

Centre contact soldered
Outer contact clamped
Weight 0.0647 kg

Environmental Data

Operating Temperature -65 °C to 165 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	
Gasket	MVQ (Silicone Rubber)	SUCOPLATE (R) Plating

Related Documents

Outline drawing DOU-00007180
Catalogue drawing DOU-00007182
Assembly instruction DOC-0000179896

Ordering Information

Single package 16_N-50-7-26/133_NE
Bulk 100 pcs package 16_N-50-7-26/133_NH

Additional Information

Suitable cables RG_213_/U, GX_07272, GX_07272_D-04

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

HUBER+SUHNER – Excellence in Connectivity Solutions



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com