

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 16_QLA-01-2-1/122_N



Description

Right angle cable plug

Interface Standards

NIM-CAMAC-Standard CD/N549



Technical Data

Electrical Data

Impedance other Ω
Interface frequency max. 1.4 GHz

Mechanical Data

Centre contact soldered
Outer contact crimped
Weight 0.0051 kg

Environmental Data

Operating Temperature -55 °C to 150 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

Centre contact
Outer contact
Body
Insulator
Crimp ferrule

Material

Brass
Brass
Brass
PFA / PTFE
Copper

Surface Plating

Gold Plating (Nickel underplated)
Nickel Plating
Nickel Plating
SUCOPLATE (R) Plating

Related Documents

Catalogue drawing DOU-00006830
Assembly instruction DOC-0000179948

Ordering Information

Single package 16_QLA-01-2-1/122_NE

Additional Information

Suitable cables RG_316_U, ENVIROFLEX_316, RG_188_A/U, RG 174 /U

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

HUBER+SUHNER – Excellence in Connectivity Solutions



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com