

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 16_QMA-50-3-3/133_N

Rev.: D



Description

Right angle cable plug

Interface Standards
QMA QLF compliant



Technical Data

Electrical Data

Impedance	50 Ω		
Interface frequency max.	6 GHz		
Frequency range	DC to 2.5 GHz	2.5 to 4 GHz	4 to 5 GHz
Return loss	≥ 32 dB	≥ 28 dB	≥ 25 dB

Mechanical Data

Centre contact	soldered
Outer contact	soldered
Weight	0.0072 kg

Environmental Data

Operating Temperature	-40 °C to 85 °C
2002/95/EC (RoHS)	compliant

Material Data

Piece Parts

Centre contact	Brass
Outer contact	Bronze
Body	Brass
Insulator	PFA / PTFE

Surface Plating

SUCOPRO Plating
SUCOPLATE (R) Plating
SUCOPRO Plating

Related Documents

Outline drawing	DOU-00005833
Catalogue drawing	DOU-00005835
Assembly instruction	DOC-0000241717

Ordering Information

Bulk 100 pcs package	16_QMA-50-3-3/133_NH
Single package	16_QMA-50-3-3/133_NE

Additional Information

Suitable cables	SUCOFORM_141, EZ_141_TP_M17, MULTIFLEX_141
-----------------	--

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions