

# HUBER+SUHNER® DATA SHEET

## Coaxial Cable Connector: 16\_SMA-50-2-106/111\_N

Rev.: B



### Description

Right angle cable plug

Interface Standards

IEC 60169-15\_MIL-STD-348A/310\_CECC 22110



### Technical Data

#### Electrical Data

Impedance 50  $\Omega$   
Interface frequency max. 18 GHz

#### Mechanical Data

Centre contact soldered  
Outer contact crimped  
Weight 0.0046 kg

#### Environmental Data

Operating Temperature -65 °C to 165 °C  
2002/95/EC (RoHS) compliant

#### Material Data

##### Piece Parts

Centre contact	Copper Beryllium Alloy
Outer contact	Copper Beryllium Alloy
Body	Brass
Insulator	PFA / PTFE
Coupling nut	Copper Beryllium Alloy
Gasket	MVQ (Silicone Rubber)
Crimp ferrule	Copper

##### Material

##### Surface Plating

Gold Plating (Nickel underplated)  
Gold Plating (Nickel underplated)  
Gold Plating (Nickel underplated)

SUCOPRO Plating

Gold Plating (without Nickel underplating)

#### Related Documents

Outline drawing	DOU-00006823
Catalogue drawing	DOU-00006406
Assembly instruction	DOC-0000178742

#### Ordering Information

Single package	16_SMA-50-2-106/111_NE
Bulk 100 pcs package	16_SMA-50-2-106/111_NH

#### Additional Information

Suitable cables K\_02252\_D, ENVIROFLEX\_316\_D, G\_02232\_D

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**