

# HUBER+SUHNER® DATA SHEET

## Coaxial Cable Connector: 21\_716-50-0-2/003\_-

Rev.: B



### Description

Straight cable jack

Interface Standards

IEC 61169-4\_CECC 22190\_DIN 47223\_VG 95250



### Technical Data

#### Electrical Data

Impedance 50  $\Omega$   
Interface frequency max. 7.5 GHz

#### Mechanical Data

Centre contact soldered  
Weight 0.1021 kg

#### Environmental Data

Operating Temperature -65 °C to 165 °C  
2002/95/EC (RoHS) compliant

#### Material Data

##### Piece Parts

Centre contact	Bronze
Outer contact	Bronze
Body	Brass
Insulator	PFA / PTFE

##### Surface Plating

Silver Plating  
Silver Plating  
SUCOPLATE (R) Plating

### Related Documents

Catalogue drawing DOU-00005933

### Ordering Information

Single package	21_716-50-0-2/003_-E
Bulk 50 pcs package	21_716-50-0-2/003_-F

### Additional Information

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**