

# HUBER+SUHNER® DATA SHEET

## Coaxial Cable Connector: 21\_716-50-10-1/003\_-

Rev.: B



### Description

Straight cable jack

Interface Standards

IEC 61169-4\_CECC 22190\_DIN 47223\_VG 95250



### Technical Data

#### Electrical Data

Impedance 50  $\Omega$   
Interface frequency max. 7.5 GHz

#### Mechanical Data

Centre contact plugged  
Outer contact crimped  
Weight 0.0853 kg

#### Environmental Data

Operating Temperature -65 °C to 165 °C  
2002/95/EC (RoHS) compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Bronze	Silver Plating
Outer contact	Brass	Silver Plating
Body	Brass	Silver Plating
Insulator	PFA / PTFE	
Crimp ferrule	Copper	SUCOPLATE (R) Plating

#### Related Documents

Outline drawing DOU-00008229  
Catalogue drawing DOU-00008231  
Assembly instruction DOC-0000183159

#### Ordering Information

Bulk 10 pcs package 21\_716-50-10-1/003\_-Z

#### Additional Information

Suitable cables S\_10162\_B-11, S\_10172\_B-11

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
**RF Technology**  
**9100 Herisau, Switzerland**  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
[www.hubersuhner.com](http://www.hubersuhner.com)

**HUBER+SUHNER – Excellence in Connectivity Solutions**