

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 21_MMCX-50-1-2/111_O

Rev.: D



Description

Straight cable jack

Interface Standards
SUHNER-MMCX

Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 6 GHz

Mechanical Data

Centre contact crimped
Outer contact crimped
Weight 0.0008 kg

Environmental Data

Operating Temperature -55 °C to 155 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

Centre contact	Copper Beryllium Alloy
Outer contact	Brass
Body	Brass
Insulator	PFA / PTFE
Crimp ferrule	Brass

Surface Plating

Gold Plating (Nickel underplated)
Gold Plating (without Nickel underplating)
Gold Plating (without Nickel underplating)
Gold Plating (without Nickel underplating)

Related Documents

Catalogue drawing DOU-00005909
Assembly instruction DOC-0000179110

Ordering Information

Single package 21_MMCX-50-1-2/111_OE

Additional Information

Suitable cable K_01152-07

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions